

**SAFETY DATA SHEET**

**1. Product And Company Identification**

SDS ID: SDS647  
PRODUCT NAME: PRESTONE® COMMAND HEAVY DUTY EXTENDED LIFE ANTIFREEZE/COOLANT  
PRODUCT NUMBER: AFC11000/F, AFC11000-55/F, AFC11000-1KL/F,  
FORMULA NUMBER: YA976, YA976-B

MANUFACTURER: Prestone Products Corporation  
Danbury, CT 06810-5109

CANADIAN OFFICE:  
FRAM Group (Canada), Inc.  
Mississauga, Ontario L5L 3S6

**MEDICAL EMERGENCIES AND ALL OTHER INFORMATION PHONE NUMBER:**

(800)890-2075 (in the US)  
(800)668-9349 (in Canada)

**TRANSPORTATION EMERGENCY PHONE NUMBER (Chemical Spills and Transport Accidents only):**

CHEMTREC 1-800-424-9300 (in the US)  
CANUTEC (613)996-6666 (in Canada)

SDS DATE OF PREPARATION/REVISION: 01/28/13

PRODUCT USE: Automobile Antifreeze – consumer and industrial product

**2. Hazards Identification**

Clear, red liquid with a characteristic odor.

**EMERGENCY OVERVIEW**

Eye and upper respiratory irritant. May cause nausea, vomiting, headache, drowsiness, blurred vision, convulsions, low blood pressure, rapid heartbeat, cyanosis, coma or death if ingested or inhaled. Prolonged or repeated skin contact may cause dermatitis or skin sensitization.

**3. Composition/Information On Ingredients**

Component	CAS No.	Amount
Ethylene Glycol	107-21-1	80-95%
Diethylene Glycol	111-46-6	0-5%
Sodium Nitrite	7632-00-0	<0.5%
Water	7732-18-5	>1%
2-Ethyl Hexanoic Acid, Sodium Salt	19766-89-3	>1%

(See Section 8 for Exposure Limits)

**4. First Aid Measures**

**INHALATION:** Remove the victim to fresh air. If breathing has stopped administer artificial respiration. If breathing is difficult, have medical personnel administer oxygen. Get medical attention.

**SKIN CONTACT:** Remove contaminated clothing. Immediately wash contacted area thoroughly with soap and water. If irritation persists, get medical attention.

**EYE CONTACT:** Immediately flush eyes with large amounts of water for 15 minutes. Get medical attention if irritation persists.

Date Prepared: 01/28/13

INGESTION: Seek immediate medical attention. Immediately call local poison control center or go to an emergency department. Never give anything by mouth to or induce vomiting in an unconscious or drowsy person.

NOTES TO PHYSICIAN: The principal toxic effects of ethylene glycol, when swallowed, are kidney damage and metabolic acidosis. The combination of metabolic acidosis, an osmol gap and oxalate crystals in the urine is evidence of ethylene glycol poisoning.

Pulmonary edema with hypoxemia has been described in a number of patients following poisoning with ethylene glycol. Respiratory support with mechanical ventilation may be required.

There may be cranial nerve involvement in the late stages of toxicity from swallowed ethylene glycol. In particular, effects have been reported involving the seventh, eighth, and ninth cranial nerves, presenting with bilateral facial paralysis, diminished hearing and dysphagia.

Ethanol is antidotal and its early administration may block the formation of nephrotoxic metabolites of ethylene glycol in the liver. The objective is to rapidly achieve and maintain a blood ethanol level of approximately 100 mg/dl by giving a loading dose of ethanol followed by a maintenance dose. Intravenous administration of ethanol is the preferred route. Ethanol blood levels should be checked frequently. Hemodialysis may be required.

4-Methyl pyrazole (Fomepizole(R)), a potent inhibitor of alcohol dehydrogenase, has been used therapeutically to decrease the metabolic consequences of ethylene glycol poisoning. Fomepizole is easier to use clinically than ethanol, does not cause CNS depression or hypoglycemia and requires less monitoring than ethanol. Additional therapeutic modalities which may decrease the adverse consequences of ethylene glycol metabolism are the administration of both thiamine and pyridoxine. As there are complicated and serious overdoses, we recommend you consult with the toxicologists at your poison control center.

The principal toxic effects of sodium nitrite poisoning are vasodilation and/or methemoglobinemia. Hypotension with syncope and tachycardia are common findings. Coronary vasospasm due to acute withdrawal may be seen. Paradoxical bradycardia may occur rarely. Coronary ischemia and cerebrovascular disease can occur due to severe hypotension. Immediate life support measures should be provided because of associated hypotension, seizures, and methemoglobinemia-induced anoxia. Immediately contact a poison center or hospital emergency department for treatment advice.

#### 5. Firefighting Measures

EXTINGUISHING MEDIA: For large fires, use alcohol type or all-purpose foams. For small fires, use water spray, carbon dioxide or dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: Do not spray pool fires directly. Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored.

UNUSUAL FIRE HAZARDS: A solid stream of water or foam directed into hot, burning liquid can cause frothing.

HAZARDOUS COMBUSTION PRODUCTS: Burning may produce carbon monoxide and carbon dioxide.

#### 6: Accidental Release Measures

Wear appropriate protective clothing and equipment (See Section 8). Collect with absorbent material and place in appropriate, labeled container for disposal or, if permitted flush spill area with water.

#### 7. Handling and Storage

DANGER: Harmful or Fatal if Swallowed

Do not drink antifreeze or solution.  
Avoid eye and prolonged or repeated skin contact.

Avoid breathing vapors or mists.  
Wash exposed skin thoroughly with soap and water after use.  
Do not store in opened or unlabeled containers.  
Keep container away from open flames and excessive heat.  
Do not reuse empty containers unless properly cleaned.  
Empty containers retain product residue and may be dangerous. Do not cut, weld, drill, etc. containers, even empty.

Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without any obvious ignition sources. Published "autoignition" or "ignition" temperatures cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Use of this product in elevated temperature applications should be thoroughly evaluated to assure safe operating conditions.

NFPA CLASSIFICATION: III B

**8. Exposure Controls / Personal Protection**

**EXPOSURE LIMITS**

CHEMICAL	EXPOSURE LIMIT
Ethylene Glycol	100 mg/m <sup>3</sup> Ceiling ACGIH TLV
Diethylene Glycol	10 mg/m <sup>3</sup> TWA AIHA WEEL
Sodium Nitrite	None Established
Water	None Established
2-Ethyl Hexanoic Acid, Sodium Salt	None Established

**VENTILATION:** Use general ventilation or local exhaust as required to maintain exposures below the occupational exposure limits.

**RESPIRATORY PROTECTION:** For operations where the TLV is exceeded a NIOSH approved respirator with organic vapor cartridges and dust/mist prefilters or supplied air respirator is recommended. Equipment selection depends on contaminant type and concentration. Select and use in accordance with 29 CFR 1910.134 and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.

**GLOVES:** Chemical resistant gloves such as neoprene or PVC where contact is possible.

**EYE PROTECTION:** Splash-proof goggles.

**OTHER PROTECTIVE EQUIPMENT/CLOTHING:** Appropriate protective clothing as needed to minimize skin contact.

**9. Physical and Chemical Properties**

**APPEARANCE AND ODOR:** Clear, red liquid with a characteristic odor. There is no odor threshold data for this product.

pH: 8.7	SPECIFIC GRAVITY: 1.11
BOILING POINT (F): 354°F (178.8°C)	VAPOR PRESSURE: Not determined
FREEZING POINT (F): -36°F (-37.7°C)	VAPOR DENSITY: Not determined
SOLUBILITY IN WATER: 100%	PERCENT VOLATILE: None
VISCOSITY: Not determined	EVAPORATION RATE: Not determined
COEFFICIENT OF WATER OIL DISTRIBUTION: Not determined	
FLASH POINT: >220°F (>104°C) TOC	AUTOIGNITION TEMP: Not determined
FLAMMABILITY LIMITS: LEL: Not determined	UEL: Not determined

**10. Stability and Reactivity**

STABILITY: Stable

CONDITIONS TO AVOID: None

INCOMPATIBILITY: Normally unreactive, however, avoid strong bases at high temperatures, strong acids, strong oxidizing agents, and materials reactive with hydroxyl compounds.

DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide.

HAZARDOUS POLYMERIZATION: Will not occur.

**11. Toxicological Information**

**POTENTIAL HEALTH EFFECTS:**

**ACUTE HAZARDS:**

INHALATION: May cause irritation of the nose and throat with headache, particularly from mists. High vapor concentrations caused, for example, by heating the material in an enclosed and poorly ventilated workplace, may produce nausea, vomiting, headache, dizziness and irregular eye movements.

SKIN CONTACT: No evidence of adverse effects from available information.

EYE CONTACT: Liquid, vapors or mist may cause discomfort in the eye with persistent conjunctivitis, seen as slight excess redness or conjunctiva. Serious corneal injury is not anticipated.

INGESTION: May cause abdominal discomfort or pain, nausea, vomiting, dizziness, drowsiness, malaise, blurring of vision, irritability, back pain, decrease in urine output, kidney failure, and central nervous system effects, including irregular eye movements, convulsions and coma. Cardiac failure and pulmonary edema may develop. Severe kidney damage which may be fatal may follow the swallowing of ethylene glycol. A few reports have been published describing the development of weakness of the facial muscles, diminishing hearing, and difficulty with swallowing, during the late stages of severe poisoning. This product contains less than 0.5% sodium nitrite. Swallowing sodium nitrite causes the formation of methemoglobin in the blood which may result in cyanosis, lowering of blood pressure, rapid heartbeat and severe headache. Doses as low as 14 mg/kg have been reported to cause toxic effects.

CHRONIC EFFECTS: Prolonged or repeated inhalation exposure may produce signs of central nervous system involvement, particularly dizziness and jerking eye movements. Prolonged or repeated skin contact may cause skin sensitization and an associated dermatitis in some individuals. Ethylene glycol has been found to cause birth defects in laboratory animals. The significance of this finding to humans has not been determined.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: The available toxicological information and knowledge of the physical and chemical properties of the material suggest that overexposure is unlikely to aggravate existing medical conditions.

CARCINOGEN: None of the components of these products is listed as a carcinogen or suspected carcinogen by IARC, NTP, ACGIH or OSHA.

**Acute Toxicity Values:**

Ethylene Glycol:	LD50 Oral Rat: 4700 mg/kg LD50 Skin Rabbit: 9530 mg/kg
Diethylene Glycol:	LD50 Oral Rat: 12,565 mg/kg LD50 Skin Rabbit: 11,890 mg/kg
Sodium Nitrite:	LD50 Oral Rat: 180 mg/kg LC50 Inhalation Rat: 5.5 mg/m <sup>3</sup> /4 hr.

SIGNIFICANT LABORATORY DATA WITH POSSIBLE RELEVANCE TO HUMAN HEALTH: Ethylene glycol has been shown to produce dose-related teratogenic effects in rats and mice when given by gavage or in drinking water at high concentrations or doses. Also, in a preliminary study to assess the effects of exposure of pregnant rats and mice to aerosols at concentrations 150, 1,000 and 2,500 mg/m<sup>3</sup> for 6 hours a day throughout the period of organogenesis, teratogenic effects were produced at the highest concentrations, but only in mice. The conditions of these latter experiments did not allow a conclusion as to whether the developmental toxicity was mediated by inhalation of aerosol, percutaneous absorption of ethylene glycol from contaminated skin, or swallowing of ethylene glycol as a result of grooming the wetted coat. In a further study, comparing effects from high aerosol concentration by whole-body or nose-only exposure, it was shown that nose-only exposure resulted in maternal toxicity (1,000 and 2,500 mg/m<sup>3</sup>) and developmental toxicity in with minimal evidence of teratogenicity (2,500 mg/m<sup>3</sup>). The no-effects concentration (based on maternal toxicity) was 500 mg/m<sup>3</sup>. In a further study in mice, no teratogenic effects could be produced when ethylene glycol was applied to the skin of pregnant mice over the period of organogenesis. The above observations suggest that ethylene glycol is to be regarded as an animal teratogen; there is currently no available information to suggest that ethylene glycol caused birth defects in humans. Cutaneous application of ethylene glycol is ineffective in producing developmental toxicity; exposure to high aerosol concentration is only minimally effective in producing developmental toxicity; the major route for producing developmental toxicity is perorally.

Two chronic feeding studies, using rats and mice, have not produced any evidence that ethylene glycol causes dose-related increases in tumor incidence or a different pattern of tumors compared with untreated controls. The absence of carcinogenic potential for ethylene glycol has been supported by numerous invitro genotoxicity studies showing that it does not produce mutagenic or clastogenic effects.

## 12. Ecological Information

Ethylene Glycol: LC50 Goldfish: 5,000 mg/L/24 hr. at 20 C static conditions.

Toxicity threshold (cell multiplication inhibition test):

Bacterial (*Pseudomonas putida*): 10,000 mg/l

Protozoa (*Entosiphon sulcatum* and *Uronema parduczi* Chatton-Lwoff): >10,000 mg/l

Algae (*Microcystis aeruginosa*): 2,000 mg/l

Green algae (*Scenedesmus quadricauda*) : >10,000 mg/l.

## 13. Disposal Considerations

Dispose of product in accordance with all local, state/provincial and federal regulations.

## 14. Transport Information

U.S. DOT HAZARD CLASSIFICATION: Not Regulated (unless package contains a reportable quantity)

Note: IF A SHIPMENT OF A REPORTABLE QUANTITY (5,260 LBS/565 GAL.) IN A SINGLE PACKAGE IS INVOLVED, THE FOLLOWING INFORMATION APPLIES:

PROPER SHIPPING NAME: RQ, Environmentally hazardous substance, liquid, n.o.s. (Ethylene glycol)

UN NUMBER: UN3082

PACKING GROUP: III

LABELS REQUIRED: Class 9

DOT MARINE POLLUTANTS: This product does not contain Marine Pollutants as defined in 49 CFR 171.8.

IMDG CODE SHIPPING CLASSIFICATION: Not Regulated

CANADIAN TDG CLASSIFICATION: Not Regulated

## 15. Regulatory Information

EPA SARA 311/312 HAZARD CLASSIFICATION: Acute health, chronic health

EPA SARA 313: This Product Contains the Following Chemicals Subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372):

Ethylene Glycol 107-21-1 80-95%

PROTECTION OF STRATOSPHERIC OZONE: This product is not known to contain or to have been manufactured with ozone depleting substances as defined in 40 CFR Part 82, Appendix A to Subpart A.

CERCLA SECTION 103: Spills of this product over the RQ (reportable quantity) must be reported to the National Response Center. The RQ for this product, based on the RQ for Ethylene Glycol (95% maximum) of 5,000 lbs, is 5,260 lbs. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

CALIFORNIA PROPOSITION 65: The normal consumer use of this product does not result in exposures to chemicals known to the State of California to cause Cancer and/or Reproductive Harm above the significant risk level for carcinogens or the maximum allowable dose levels for reproductive toxins. Therefore, no warnings are required for consumer packages. Industrial or other occupational use of this product at higher frequency and using larger quantities of this product may result in exposures exceeding these levels and are labeled accordingly.

EPA TSCA INVENTORY: All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

CANADIAN ENVIRONMENTAL PROTECTION ACT: All of the ingredients are listed on the Canadian Domestic Substances List.

CANADIAN WHMIS CLASSIFICATION: Class D - Division 2 - Subdivision A - (A very toxic material causing other toxic effects)



CANADIAN WHMIS HAZARD SYMBOLS:

This SDS has been prepared according to the criteria of the Controlled Products Regulation (CPR) and the SDS contains all of the information required by the CPR.

EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES (EINECS): All of the ingredients are listed on the EINECS inventory.

JAPAN: All of the ingredients of this product are listed on the Japanese Existing and New Chemical Substances (MITI) List.

AUSTRALIA: One of the ingredients of this product is not listed on the Australian Inventory of Chemical Substances (AICS).

KOREA: All of the ingredients of this product are listed on the Korean Existing Chemical List (KECL).

CHINA: All of the ingredients of this product are listed on the Inventory of Existing Chemical Substance in China (IECSC).

<b>16. Other Information</b>
------------------------------

NFPA Rating: Fire: 1

Health: 2

Reactivity: 0

REVISION SUMMARY: New SDS

**Date Prepared: 01/28/13**

This SDS is directed to professional users and bulk handlers of the product. Consumer products are labeled in accordance with Federal Hazardous Substances Act regulations.

While Prestone Products Corporation believes that the data contained herein are factual and the opinions expressed are those of qualified experts regarding the results of tests conducted, the data are not to be taken as a warranty or representation for which Prestone Products Corporation assumes legal responsibility. They are offered for your consideration, investigation and verification. Any use of these data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

If more information is needed, please contact:

Prestone Products Corporation  
69 Eagle Road  
Danbury, CT 06810  
(800) 890-2075

**SAFETY DATA SHEET**

**1. Product And Company Identification**

SDS ID: SDS648  
PRODUCT NAME: PRESTONE® COMMAND HEAVY DUTY PREDILUTED 50/50 EXTENDED LIFE  
ANTIFREEZE/COOLANT  
PRODUCT NUMBER: AFC11100/F, AFC11100-55/F, AFC11100-1KL/F  
FORMULA NUMBER: YA-976-P50, YA-976-P50-B

MANUFACTURER: Prestone Products Corporation  
Danbury, CT 06810-5109  
CANADIAN OFFICE: FRAM Group (Canada), Inc.  
Mississauga, Ontario L5L 3S6

MEDICAL EMERGENCIES AND ALL OTHER INFORMATION PHONE NUMBER:  
(800)890-2075 (in the US)  
(800)668-9349 (in Canada)

TRANSPORTATION EMERGENCY PHONE NUMBER (Chemical Spills and Transport Accidents only):  
CHEMTREC 1-800-424-9300 (in the US)  
CANUTEC (613)996-6666 (in Canada)

SDS DATE OF PREPARATION/REVISION: 02/05/13  
PRODUCT USE: Automobile Antifreeze – consumer product

**2. Hazards Identification**

Clear, red liquid with a characteristic odor.

**EMERGENCY OVERVIEW**

Eye and upper respiratory irritant. May cause nausea, vomiting, headache, drowsiness, blurred vision, convulsions, low blood pressure, rapid heartbeat, cyanosis, coma or death if ingested or inhaled. Prolonged or repeated skin contact may cause dermatitis or skin sensitization.

**3. Composition/Information On Ingredients**

Component	CAS No.	Amount
Ethylene Glycol	107-21-1	40-50%
Diethylene Glycol	111-46-6	0-3%
Sodium Nitrite	7632-00-0	<0.5%
2-Ethyl Hexanoic Acid, Sodium Salt	19766-89-3	0-5%
Water	7732-18-5	50-60%

(See Section 8 for Exposure Limits)

**4. First Aid Measures**

**INHALATION:** Remove the victim to fresh air. If breathing has stopped administer artificial respiration. If breathing is difficult, have medical personnel administer oxygen. Get medical attention.

**SKIN CONTACT:** Remove contaminated clothing. Immediately wash contacted area thoroughly with soap and water. If irritation persists, get medical attention.

**EYE CONTACT:** Immediately flush eyes with large amounts of water for 15 minutes. Get medical attention if irritation persists.



**INGESTION:** Seek immediate medical attention. Immediately call local poison control center or go to an emergency department. Never give anything by mouth to or induce vomiting in an unconscious or drowsy person.

**NOTES TO PHYSICIAN:** The principal toxic effects of ethylene glycol, when swallowed, are kidney damage and metabolic acidosis. The combination of metabolic acidosis, an osmol gap and oxalate crystals in the urine is evidence of ethylene glycol poisoning.

Pulmonary edema with hypoxemia has been described in a number of patients following poisoning with ethylene glycol. Respiratory support with mechanical ventilation may be required.

There may be cranial nerve involvement in the late stages of toxicity from swallowed ethylene glycol. In particular, effects have been reported involving the seventh, eighth, and ninth cranial nerves, presenting with bilateral facial paralysis, diminished hearing and dysphagia.

Ethanol is antidotal and its early administration may block the formation of nephrotoxic metabolites of ethylene glycol in the liver. The objective is to rapidly achieve and maintain a blood ethanol level of approximately 100 mg/dl by giving a loading dose of ethanol followed by a maintenance dose. Intravenous administration of ethanol is the preferred route. Ethanol blood levels should be checked frequently. Hemodialysis may be required.

4-Methyl pyrazole (Fomepizole(R)), a potent inhibitor of alcohol dehydrogenase, has been used therapeutically to decrease the metabolic consequences of ethylene glycol poisoning. Fomepizole is easier to use clinically than ethanol, does not cause CNS depression or hypoglycemia and requires less monitoring than ethanol. Additional therapeutic modalities which may decrease the adverse consequences of ethylene glycol metabolism are the administration of both thiamine and pyridoxine. As there are complicated and serious overdoses, we recommend you consult with the toxicologists at your poison control center.

The principal toxic effects of sodium nitrite poisoning are vasodilation and/or methemoglobinemia. Hypotension with syncope and tachycardia are common findings. Coronary vasospasm due to acute withdrawal may be seen. Paradoxical bradycardia may occur rarely. Coronary ischemia and cerebrovascular disease can occur due to severe hypotension. Immediate life support measures should be provided because of associated hypotension, seizures, and methemoglobinemia-induced anoxia. Immediately contact a poison center or hospital emergency department for treatment advice.

## **5. Firefighting Measures**

**EXTINGUISHING MEDIA:** For large fires, use alcohol type or all-purpose foams. For small fires, use water spray, carbon dioxide or dry chemical.

**SPECIAL FIRE FIGHTING PROCEDURES:** Do not spray pool fires directly. Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored.

**UNUSUAL FIRE HAZARDS:** A solid stream of water or foam directed into hot, burning liquid can cause frothing.

**HAZARDOUS COMBUSTION PRODUCTS:** Burning may produce carbon monoxide and carbon dioxide.

## **6: Accidental Release Measures**

Wear appropriate protective clothing and equipment (See Section 8). Collect with absorbent material and place in appropriate, labeled container for disposal or, if permitted flush spill area with water.

## **7. Handling and Storage**

**DANGER:** Harmful or Fatal if Swallowed

Do not drink antifreeze or solution.

Avoid eye and prolonged or repeated skin contact.  
 Avoid breathing vapors or mists.  
 Wash exposed skin thoroughly with soap and water after use.  
 Do not store in opened or unlabeled containers.  
 Keep container away from open flames and excessive heat.  
 Do not reuse empty containers unless properly cleaned.  
 Empty containers retain product residue and may be dangerous. Do not cut, weld, drill, etc. containers, even empty.

Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without any obvious ignition sources. Published "autoignition" or "ignition" temperatures cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Use of this product in elevated temperature applications should be thoroughly evaluated to assure safe operating conditions.

NFPA CLASSIFICATION: III B

**8. Exposure Controls / Personal Protection**

**EXPOSURE LIMITS**

CHEMICAL	EXPOSURE LIMIT
Ethylene Glycol	100 mg/m <sup>3</sup> Ceiling ACGIH TLV
Diethylene Glycol	None Established
Sodium Nitrite	None Established
2-Ethyl Hexanoic Acid, Sodium Salt	None Established

**VENTILATION:** Use general ventilation or local exhaust as required to maintain exposures below the occupational exposure limits.

**RESPIRATORY PROTECTION:** For operations where the TLV is exceeded a NIOSH approved respirator with organic vapor cartridges and dust/mist prefilters or supplied air respirator is recommended. Equipment selection depends on contaminant type and concentration. Select and use in accordance with 29 CFR 1910.134 and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.

**GLOVES:** Chemical resistant gloves such as neoprene or PVC where contact is possible.

**EYE PROTECTION:** Splash-proof goggles.

**OTHER PROTECTIVE EQUIPMENT/CLOTHING:** Appropriate protective clothing as needed to minimize skin contact.

**9. Physical and Chemical Properties**

**APPEARANCE AND ODOR:** Clear, red liquid with a characteristic odor. There is no odor threshold data for this product.

pH: 8.7	SPECIFIC GRAVITY: 1.07
BOILING POINT (F): 229°F (109.4°C)	VAPOR PRESSURE: Not determined
FREEZING POINT (F): -34°F (-36.6°C)	VAPOR DENSITY: Not determined
SOLUBILITY IN WATER: 100%	PERCENT VOLATILE: None
VISCOSITY: Not determined	EVAPORATION RATE: Not determined
COEFFICIENT OF WATER OIL DISTRIBUTION: Not determined	
FLASH POINT: >220°F (104.4°C) TOC	AUTOIGNITION TEMP: Not determined
FLAMMABILITY LIMITS: LEL: Not determined	UEL: Not determined

**10. Stability and Reactivity**

STABILITY: Stable

CONDITIONS TO AVOID: None

INCOMPATIBILITY: Normally unreactive, however, avoid strong bases at high temperatures, strong acids, strong oxidizing agents, and materials reactive with hydroxyl compounds.

DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide.

HAZARDOUS POLYMERIZATION: Will not occur.

**11. Toxicological Information**

**POTENTIAL HEALTH EFFECTS:**

**ACUTE HAZARDS:**

INHALATION: May cause irritation of the nose and throat with headache, particularly from mists. High vapor concentrations caused, for example, by heating the material in an enclosed and poorly ventilated workplace, may produce nausea, vomiting, headache, dizziness and irregular eye movements.

SKIN CONTACT: No evidence of adverse effects from available information.

EYE CONTACT: Liquid, vapors or mist may cause discomfort in the eye with persistent conjunctivitis, seen as slight excess redness or conjunctiva. Serious corneal injury is not anticipated.

INGESTION: May cause abdominal discomfort or pain, nausea, vomiting, dizziness, drowsiness, malaise, blurring of vision, irritability, back pain, decrease in urine output, kidney failure, and central nervous system effects, including irregular eye movements, convulsions and coma. Cardiac failure and pulmonary edema may develop. Severe kidney damage which may be fatal may follow the swallowing of ethylene glycol. A few reports have been published describing the development of weakness of the facial muscles, diminishing hearing, and difficulty with swallowing, during the late stages of severe poisoning. This product contains less than 0.5% sodium nitrite. Swallowing sodium nitrite causes the formation of methemoglobin in the blood which may result in cyanosis, lowering of blood pressure, rapid heartbeat and severe headache. Doses as low as 14 mg/kg have been reported to cause toxic effects.

CHRONIC EFFECTS: Prolonged or repeated inhalation exposure may produce signs of central nervous system involvement, particularly dizziness and jerking eye movements. Prolonged or repeated skin contact may cause skin sensitization and an associated dermatitis in some individuals. Ethylene glycol has been found to cause birth defects in laboratory animals. The significance of this finding to humans has not been determined.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: The available toxicological information and knowledge of the physical and chemical properties of the material suggest that overexposure is unlikely to aggravate existing medical conditions.

CARCINOGEN: None of the components of these products is listed as a carcinogen or suspected carcinogen by IARC, NTP, ACGIH or OSHA.

**ACUTE TOXICITY VALUES:**

Ethylene Glycol:	LD50 Oral Rat: 4700 mg/kg LD50 Skin Rabbit: 9530 mg/kg
Diethylene Glycol:	LD50 Oral Rat: 12,565 mg/kg LD50 Skin Rabbit: 11,890 mg/kg
Sodium Nitrite:	LD50 Oral Rat: 180 mg/kg LC50 Inhalation Rat: 5.5 mg/m <sup>3</sup> /4 hr.

**Date Prepared: 02/05/2013**

**SIGNIFICANT LABORATORY DATA WITH POSSIBLE RELEVANCE TO HUMAN HEALTH:** Ethylene glycol has been shown to produce dose-related teratogenic effects in rats and mice when given by gavage or in drinking water at high concentrations or doses. Also, in a preliminary study to assess the effects of exposure of pregnant rats and mice to aerosols at concentrations 150, 1,000 and 2,500 mg/m<sup>3</sup> for 6 hours a day throughout the period of organogenesis, teratogenic effects were produced at the highest concentrations, but only in mice. The conditions of these latter experiments did not allow a conclusion as to whether the developmental toxicity was mediated by inhalation of aerosol, percutaneous absorption of ethylene glycol from contaminated skin, or swallowing of ethylene glycol as a result of grooming the wetted coat. In a further study, comparing effects from high aerosol concentration by whole-body or nose-only exposure, it was shown that nose-only exposure resulted in maternal toxicity (1,000 and 2,500 mg/m<sup>3</sup>) and developmental toxicity in with minimal evidence of teratogenicity (2,500 mg/m<sup>3</sup>). The no-effects concentration (based on maternal toxicity) was 500 mg/m<sup>3</sup>. In a further study in mice, no teratogenic effects could be produced when ethylene glycol was applied to the skin of pregnant mice over the period of organogenesis. The above observations suggest that ethylene glycol is to be regarded as an animal teratogen; there is currently no available information to suggest that ethylene glycol caused birth defects in humans. Cutaneous application of ethylene glycol is ineffective in producing developmental toxicity; exposure to high aerosol concentration is only minimally effective in producing developmental toxicity; the major route for producing developmental toxicity is perorally.

Two chronic feeding studies, using rats and mice, have not produced any evidence that ethylene glycol causes dose-related increases in tumor incidence or a different pattern of tumors compared with untreated controls. The absence of carcinogenic potential for ethylene glycol has been supported by numerous invitro genotoxicity studies showing that it does not produce mutagenic or clastogenic effects.

## 12. Ecological Information

Ethylene Glycol: LC50 Goldfish: 5,000 mg/L/24 hr. at 20 C static conditions.

Toxicity threshold (cell multiplication inhibition test):

Bacterial (*Pseudomonas putida*): 10,000 mg/l

Protozoa (*Entosiphon sulcatum* and *Uronema parduczi* Chatton-Lwoff): >10,000 mg/l

Algae (*Microcystis aeruginosa*): 2,000 mg/l

Green algae (*Scenedesmus quadricauda*): >10,000 mg/l.

## 13. Disposal Considerations

Dispose of product in accordance with all local, state/provincial and federal regulations.

## 14. Transport Information

U.S. DOT HAZARD CLASSIFICATION: Not Regulated (unless package contains a reportable quantity)

Note: IF A SHIPMENT OF A REPORTABLE QUANTITY (10,000 LBS/1,119 GAL.) IN A SINGLE PACKAGE IS INVOLVED, THE FOLLOWING INFORMATION APPLIES:

PROPER SHIPPING NAME: RQ, Environmentally hazardous substance, liquid, n.o.s. (Ethylene glycol)

UN NUMBER: UN3082

PACKING GROUP: III

LABELS REQUIRED: Class 9

DOT MARINE POLLUTANTS: This product does not contain Marine Pollutants as defined in 49 CFR 171.8.

IMDG CODE SHIPPING CLASSIFICATION: Not Regulated

CANADIAN TDG CLASSIFICATION: Not Regulated

## 15. Regulatory Information

EPA SARA 311/312 HAZARD CLASSIFICATION: Acute health, chronic health

EPA SARA 313: This Product Contains the Following Chemicals Subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372):

Ethylene Glycol 107-21-1 80-95%

PROTECTION OF STRATOSPHERIC OZONE: This product is not known to contain or to have been manufactured with ozone depleting substances as defined in 40 CFR Part 82, Appendix A to Subpart A.

CERCLA SECTION 103: Spills of this product over the RQ (reportable quantity) must be reported to the National Response Center. The RQ for this product, based on the RQ for Ethylene Glycol (50% maximum) of 5,000 lbs, is 10,000 lbs. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

CALIFORNIA PROPOSITION 65: The normal consumer use of this product does not result in exposures to chemicals known to the State of California to cause Cancer and/or Reproductive Harm above the significant risk level for carcinogens or the maximum allowable dose levels for reproductive toxins. Therefore, no warnings are required for consumer packages. Industrial or other occupational use of this product at higher frequency and using larger quantities of this product may result in exposures exceeding these levels and are labeled accordingly.

EPA TSCA INVENTORY: All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

CANADIAN ENVIRONMENTAL PROTECTION ACT: All of the ingredients are listed on the Canadian Domestic Substances List.

CANADIAN WHMIS CLASSIFICATION: Class D - Division 2 - Subdivision A - (A very toxic material causing other toxic effects)



CANADIAN WHMIS HAZARD SYMBOLS:

This SDS has been prepared according to the criteria of the Controlled Products Regulation (CPR) and the SDS contains all of the information required by the CPR.

EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES (EINECS): All of the ingredients are listed on the EINECS inventory.

JAPAN: All of the ingredients of this product are listed on the Japanese Existing and New Chemical Substances (MITI) List.

AUSTRALIA: One of the ingredients of this product is not listed on the Australian Inventory of Chemical Substances (AICS).

KOREA: All of the ingredients of this product are listed on the Korean Existing Chemical List (KECL).

CHINA: All of the ingredients of this product are listed on the Inventory of Existing Chemical Substance in China (IECSC).

#### 16. Other Information

NFPA Rating: Fire: 1

Health: 2

Reactivity: 0

REVISION SUMMARY: Changes to Sections 14, and 15: Reportable quantities.

This SDS is directed to professional users and bulk handlers of the product. Consumer products are labeled in accordance with Federal Hazardous Substances Act regulations.



**SDS648**  
**PRESTONE® COMMAND HEAVY DUTY PREDILUTED**  
**50/50 EXTENDED LIFE ANTIFREEZE/COOLANT**  
**Date Prepared: 02/05/2013**

While Prestone Products Corporation believes that the data contained herein are factual and the opinions expressed are those of qualified experts regarding the results of tests conducted, the data are not to be taken as a warranty or representation for which Prestone Products Corporation assumes legal responsibility. They are offered for your consideration, investigation and verification. Any use of these data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

If more information is needed, please contact:

Prestone Products Corporation  
69 Eagle Road  
Danbury, CT 06810  
(800) 890-2075

**SAFETY DATA SHEET**

**1. Product And Company Identification**

SDS ID: SDS649  
PRODUCT NAME: Prestone ® Command Heavy Duty Antifreeze/Coolant  
PRODUCT NUMBER: AFC10000/F, AFC10000-55/F, AFC10000-1KL/F  
FORMULA NUMBER: YA-987-V, YA-987-V-B

MANUFACTURER: Prestone Products Corporation  
Danbury, CT 06810-5109  
CANADIAN OFFICE: FRAM Group (Canada), Inc.  
Mississauga, Ontario L5L 3S6

MEDICAL EMERGENCIES AND ALL OTHER INFORMATION PHONE NUMBER:  
(800)890-2075 (in the US)  
(800)668-9349 (in Canada)

TRANSPORTATION EMERGENCY PHONE NUMBER (Chemical Spills and Transport Accidents only):  
CHEMTREC 1-800-424-9300 (in the US)  
CANUTEC (613)996-6666 (in Canada)

SDS DATE OF PREPARATION/REVISION: 01/28/13

PRODUCT USE: Automobile antifreeze – consumer and industrial product

**2. Hazards Identification**

Clear, dyed liquid with a characteristic odor.

**EMERGENCY OVERVIEW**

Eye and upper respiratory irritant. May cause nausea, vomiting, headache, drowsiness, blurred vision, convulsions, coma or death if ingested or inhaled. Prolonged or repeated skin contact may cause dermatitis or skin sensitization.

**3. Composition/Information On Ingredients**

Component	CAS No.	Amount
Ethylene Glycol	107-21-1	95-100
Diethylene Glycol	111-46-6	0-5
Sodium Nitrite	7632-00-0	<0.5

(See Section 8 for Exposure Limits)

**4. First Aid Measures**

**INHALATION:** Remove the victim to fresh air. If breathing has stopped administer artificial respiration. If breathing is difficult, have medical personnel administer oxygen. Get medical attention.

**SKIN CONTACT:** Remove contaminated clothing. Immediately wash contacted area thoroughly with soap and water. If irritation persists, get medical attention.

**EYE CONTACT:** Immediately flush eyes with large amounts of water for 15 minutes. Get medical attention if irritation persists.

INGESTION: Seek immediate medical attention. Immediately call local poison control center or go to an emergency department. Never give anything by mouth to or induce vomiting in an unconscious or drowsy person.

NOTES TO PHYSICIAN: The principal toxic effects of ethylene glycol, when swallowed, are kidney damage and metabolic acidosis. The combination of metabolic acidosis, an osmol gap and oxalate crystals in the urine is evidence of ethylene glycol poisoning.

Pulmonary edema with hypoxemia has been described in a number of patients following poisoning with ethylene glycol. Respiratory support with mechanical ventilation may be required.

There may be cranial nerve involvement in the late stages of toxicity from swallowed ethylene glycol. In particular, effects have been reported involving the seventh, eighth, and ninth cranial nerves, presenting with bilateral facial paralysis, diminished hearing and dysphagia.

Ethanol is antidotal and its early administration may block the formation of nephrotoxic metabolites of ethylene glycol in the liver. The objective is to rapidly achieve and maintain a blood ethanol level of approximately 100 mg/dl by giving a loading dose of ethanol followed by a maintenance dose. Intravenous administration of ethanol is the preferred route. Ethanol blood levels should be checked frequently. Hemodialysis may be required.

4-Methyl pyrazole (Fomepizole®), a potent inhibitor of alcohol dehydrogenase, has been used therapeutically to decrease the metabolic consequences of ethylene glycol poisoning. Fomepizole® is easier to use clinically than ethanol, does not cause CNS depression or hypoglycemia and requires less monitoring than ethanol. Additional therapeutic modalities which may decrease the adverse consequences of ethylene glycol metabolism are the administration of both thiamine and pyridoxine. As there are complicated and serious overdoses, we recommend you consult with the toxicologists at your poison control center.

The principal toxic effects of sodium nitrite poisoning are vasodilation and/or methemoglobinemia. Hypotension with syncope and tachycardia are common findings. Coronary vasospasm due to acute withdrawal may be seen. Paradoxical bradycardia may occur rarely. Coronary ischemia and cerebrovascular disease can occur due to severe hypotension. Immediate life support measures should be provided because of associated hypotension, seizures, and methemoglobinemia-induced anoxia. Immediately contact a poison center or hospital emergency department for treatment advice.

## 5. Firefighting Measures

EXTINGUISHING MEDIA: For large fires, use alcohol type or all-purpose foams. For small fires, use water spray, carbon dioxide or dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: Do not spray pool fires directly. Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored.

UNUSUAL FIRE HAZARDS: A solid stream of water or foam directed into hot, burning liquid can cause frothing.

HAZARDOUS COMBUSTION PRODUCTS: Burning may produce carbon monoxide and carbon dioxide.

## 6: Accidental Release Measures

Wear appropriate protective clothing and equipment (See Section 8). Collect with absorbent material and place in appropriate, labeled container for disposal or, if permitted flush spill area with water.

## 7. Handling and Storage

DANGER: Harmful or Fatal if Swallowed

Do not drink antifreeze or solution.



Avoid eye and prolonged or repeated skin contact.  
 Avoid breathing vapors or mists.  
 Wash exposed skin thoroughly with soap and water after use.  
 Do not store in opened or unlabeled containers.  
 Keep container away from open flames and excessive heat.  
 Do not reuse empty containers unless properly cleaned.  
 Empty containers retain product residue and may be dangerous. Do not cut, weld, drill, etc. containers, even empty.

Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without any obvious ignition sources. Published "autoignition" or "ignition" temperatures cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Use of this product in elevated temperature applications should be thoroughly evaluated to assure safe operating conditions.

NFPA CLASSIFICATION: III B

**8. Exposure Controls / Personal Protection**

**EXPOSURE LIMITS**

CHEMICAL	EXPOSURE LIMIT
Ethylene Glycol (as aerosol)	100 mg/m <sup>3</sup> Ceiling ACGIH TLV
Diethylene Glycol	None Established
Sodium Nitrite	None Established

**VENTILATION:** Use general ventilation or local exhaust as required to maintain exposures below the occupational exposure limits.

**RESPIRATORY PROTECTION:** For operations where the TLV is exceeded a NIOSH approved respirator with organic vapor cartridges and dust/mist prefilters or supplied air respirator is recommended. Equipment selection depends on contaminant type and concentration. Select and use in accordance with 29 CFR 1910.134 and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.

**GLOVES:** Chemical resistant gloves such as neoprene or PVC where contact is possible.

**EYE PROTECTION:** Splash-proof goggles.

**OTHER PROTECTIVE EQUIPMENT/CLOTHING:** Appropriate protective clothing as needed to minimize skin contact.

**9. Physical and Chemical Properties**

**APPEARANCE AND ODOR:** Clear, green or purple liquid with a characteristic odor. There is no odor threshold data for this product.

pH: Not determined	SPECIFIC GRAVITY: 1.115
BOILING POINT: 387°F (197.2°C)	VAPOR PRESSURE: < 0.06 mmHg @ 20°C
FREEZING POINT: 8°F (-13.3°C)	VAPOR DENSITY: 2.1
SOLUBILITY IN WATER: 100%	EVAPORATION RATE: Not determined
PERCENT VOLATILE: None	VISCOSITY: Not determined
FLASH POINT: >241°F (>116.1°C) TCC	AUTOIGNITION TEMPERATURE: 748°F (estimated)
FLAMMABILITY LIMITS: LEL: 3.2% (ethylene glycol) UEL: 15.3% (ethylene glycol)	
COEFFICIENT OF WATER/OIL DISTRIBUTION: Not determined	

## 10. Stability and Reactivity

STABILITY: Stable

CONDITIONS TO AVOID: None

INCOMPATIBILITY: Normally un-reactive, however, avoid strong bases at high temperatures, strong acids, strong oxidizing agents, and materials reactive with hydroxyl compounds.

DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide.

HAZARDOUS POLYMERIZATION: Will not occur.

## 11. Toxicological Information

### POTENTIAL HEALTH EFFECTS:

#### ACUTE HAZARDS:

INHALATION: May cause irritation of the nose and throat with headache, particularly from mists. High vapor concentrations caused, for example, by heating the material in an enclosed and poorly ventilated workplace, may produce nausea, vomiting, headache, dizziness and irregular eye movements.

SKIN CONTACT: No evidence of adverse effects from available information.

EYE CONTACT: Liquid, vapors or mist may cause discomfort in the eye with persistent conjunctivitis, seen as slight excess redness or conjunctiva. Serious corneal injury is not anticipated.

INGESTION: May cause abdominal discomfort or pain, nausea, vomiting, dizziness, drowsiness, malaise, blurring of vision, irritability, back pain, decrease in urine output, kidney failure, and central nervous system effects, including irregular eye movements, convulsions and coma. Cardiac failure and pulmonary edema may develop. Severe kidney damage which may be fatal may follow the swallowing of ethylene glycol. A few reports have been published describing the development of weakness of the facial muscles, diminishing hearing, and difficulty with swallowing, during the late stages of severe poisoning. This product contains less than 0.5% sodium nitrite. Swallowing sodium nitrite causes the formation of methemoglobin in the blood which may result in cyanosis, lowering of blood pressure, rapid heartbeat and severe headache. Doses as low as 14 mg/kg have been reported to cause toxic effects.

CHRONIC EFFECTS: Prolonged or repeated inhalation exposure may produce signs of central nervous system involvement, particularly dizziness and jerking eye movements. Prolonged or repeated skin contact may cause skin sensitization and an associated dermatitis in some individuals. Ethylene glycol has been found to cause birth defects in laboratory animals. The significance of this finding to humans has not been determined.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: The available toxicological information and a knowledge of the physical and chemical properties of the material suggest that overexposure is unlikely to aggravate existing medical conditions.

CARCINOGEN: None of the components of these products is listed as a carcinogen or suspected carcinogen by IARC, NTP, ACGIH or OSHA.

#### Acute Toxicity Values:

Ethylene Glycol: LD50 Oral Rat: 4700 mg/kg;  
LD50 Skin Rabbit: 9530 mg/kg

Diethylene Glycol: LD50 Oral Rat: 12,565 mg/kg;  
LD50 Skin Rabbit: 11,890 mg/kg

Sodium Nitrite: LD50 Oral Rat: 180 mg/kg;

LC50 Inhalation Rat: 5.5 mg/m<sup>3</sup>/4 hr.

**SIGNIFICANT LABORATORY DATA WITH POSSIBLE RELEVANCE TO HUMAN HEALTH:** Ethylene glycol has been shown to produce dose-related teratogenic effects in rats and mice when given by gavage or in drinking water at high concentrations or doses. Also, in a preliminary study to assess the effects of exposure of pregnant rats and mice to aerosols at concentrations 150, 1,000 and 2,500 mg/m<sup>3</sup> for 6 hours a day throughout the period of organogenesis, teratogenic effects were produced at the highest concentrations, but only in mice. The conditions of these latter experiments did not allow a conclusion as to whether the developmental toxicity was mediated by inhalation of aerosol, percutaneous absorption of ethylene glycol from contaminated skin, or swallowing of ethylene glycol as a result of grooming the wetted coat. In a further study, comparing effects from high aerosol concentration by whole-body or nose-only exposure, it was shown that nose-only exposure resulted in maternal toxicity (1,000 and 2,500 mg/m<sup>3</sup>) and developmental toxicity in with minimal evidence of teratogenicity (2,500 mg/m<sup>3</sup>). The no-effects concentration (based on maternal toxicity) was 500 mg/m<sup>3</sup>. In a further study in mice, no teratogenic effects could be produced when ethylene glycol was applied to the skin of pregnant mice over the period of organogenesis. The above observations suggest that ethylene glycol is to be regarded as an animal teratogen; there is currently no available information to suggest that ethylene glycol caused birth defects in humans. Cutaneous application of ethylene glycol is ineffective in producing developmental toxicity; exposure to high aerosol concentration is only minimally effective in producing developmental toxicity; the major route for producing developmental toxicity is perorally.

Two chronic feeding studies, using rats and mice, have not produced any evidence that ethylene glycol causes dose-related increases in tumor incidence or a different pattern of tumors compared with untreated controls. The absence of carcinogenic potential for ethylene glycol has been supported by numerous invitro genotoxicity studies showing that it does not produce mutagenic or clastogenic effects.

## 12. Ecological Information

Ethylene Glycol: LC50 Goldfish: 5,000 mg/L/24 hr. at 20 C static conditions.

Toxicity threshold (cell multiplication inhibition test):

Bacterial (*Pseudomonas putida*): 10,000 mg/l;

Protozoa (*Entosiphon sulcatum* and *Uronema parduczi*; *Chatton-Lwoff*): >10,000 mg/l;

Algae (*Microcystis aeruginosa*): 2,000 mg/l;

Green algae (*Scenedesmus quadricauda*): >10,000 mg/l

## 13. Disposal Considerations

Dispose of product in accordance with all local, state/provincial and federal regulations.

## 14. Transport Information

U.S. DOT HAZARD CLASSIFICATION: Not Regulated (unless package contains a reportable quantity)

Note: IF A SHIPMENT OF A REPORTABLE QUANTITY (5,000 LBS/538 GAL) IN A SINGLE PACKAGE IS INVOLVED, THE FOLLOWING INFORMATION APPLIES:

PROPER SHIPPING NAME: RQ, Environmentally hazardous substance, liquid, n.o.s. (Ethylene glycol)

UN NUMBER: UN3082

PACKING GROUP: III

LABELS REQUIRED: Class 9

DOT MARINE POLLUTANTS: This product does not contain Marine Pollutants as defined in 49 CFR 171.8.

IMDG CODE SHIPPING CLASSIFICATION: Not Regulated

CANADIAN TDG CLASSIFICATION: Not Regulated

**15. Regulatory Information**

EPA SARA 311/312 HAZARD CLASSIFICATION: Acute health, chronic health

EPA SARA 313: This Product Contains the Following Chemicals Subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372):

Ethylene Glycol	107-21-1	95-100%
-----------------	----------	---------

PROTECTION OF STRATOSPHERIC OZONE: This product is not known to contain or to have been manufactured with ozone depleting substances as defined in 40 CFR Part 82, Appendix A to Subpart A.

CERCLA SECTION 103: Spills of this product over the RQ (reportable quantity) must be reported to the National Response Center. The RQ for this product, based on the RQ for Ethylene Glycol (100% maximum) of 5,000 lbs., is 5,000 lbs. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

CALIFORNIA PROPOSITION 65: The normal consumer use of this product does not result in exposures to chemicals known to the State of California to cause Cancer and/or Reproductive Harm above the significant risk level for carcinogens or the maximum allowable dose levels for reproductive toxins. Therefore, no warnings are required for consumer packages. Industrial or other occupational use of this product at higher frequency and using larger quantities of this product may result in exposures exceeding these levels and are labeled accordingly.

EPA TSCA INVENTORY: All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

CANADIAN ENVIRONMENTAL PROTECTION ACT: All of the ingredients are listed on the Canadian Domestic Substances List.

CANADIAN WHMIS CLASSIFICATION: Class D - Division 2 - Subdivision A - (A very toxic material causing other toxic effects)



CANADIAN WHMIS HAZARD SYMBOLS:

This SDS has been prepared according to the criteria of the Controlled Products Regulation (CPR) and the SDS contains all of the information required by the CPR.

**16. Other Information**

NFPA RATING (NFPA 704) - FIRE: 1      HEALTH: 2      REACTIVITY: 0

REVISION SUMMARY: NEW SDS

This SDS is directed to professional users and bulk handlers of the product. Consumer products are labeled in accordance with Federal Hazardous Substances Act regulations.



While Prestone Products Corporation believes that the data contained herein are factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the data are not to be taken as a warranty or representation for which Prestone Products Corporation assumes legal responsibility. They are offered solely for your consideration, investigation and verification. Any use of these data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

If more information is needed, please contact:      Prestone Products Corporation  
69 Eagle Road  
Danbury, CT 06810  
(800) 890-2075

**SAFETY DATA SHEET**

**1. Product And Company Identification**

SDS ID: SDS650  
PRODUCT NAME: Prestone ® Command Heavy Duty Prediluted 50/50 Antifreeze / Coolant  
PRODUCT NUMBER: AFC10100/F, AFC10100-55/F, AFC10100-1KL/F  
FORMULA NUMBER: YA-987V-P50, YA-987V-P50-B

MANUFACTURER:  
Prestone Products Corporation  
Danbury, CT 06810-5109

CANADIAN OFFICE:  
FRAM Group (Canada), Inc.  
Mississauga, Ontario L5L 3S6

MEDICAL EMERGENCIES AND ALL OTHER INFORMATION PHONE NUMBER:

(800)890-2075 (in the US)  
(800)668-9349 (in Canada)

TRANSPORTATION EMERGENCY PHONE NUMBER (Chemical Spills and Transport Accidents only):

CHEMTREC 1-800-424-9300 (in the US)  
CANUTEC (613)996-6666 (in Canada)

CHEMTREC 1-703-527-3887 (outside US)

SDS DATE OF PREPARATION/REVISION: 01/30/13

PRODUCT USE: Automobile antifreeze – consumer product

**2. Hazards Identification**

Clear, dyed liquid with a characteristic odor.

**EMERGENCY OVERVIEW**

Eye and upper respiratory irritant. May cause nausea, vomiting, headache, drowsiness, blurred vision, convulsions, coma or death if ingested or inhaled. Prolonged or repeated skin contact may cause dermatitis or skin sensitization.

**3. Composition/Information on Ingredients**

Component	CAS No.	Amount
Ethylene Glycol	107-21-1	47-50%
Diethylene Glycol	111-46-6	0-3%
Sodium Nitrite	7632-00-0	< 0.3%
Water	7732-18-5	0-50%

(See Section 8 for Exposure Limits)

**4. First Aid Measures**

**INHALATION:** Remove the victim to fresh air. If breathing has stopped administer artificial respiration. If breathing is difficult, have medical personnel administer oxygen. Get medical attention.

**SKIN CONTACT:** Remove contaminated clothing. Immediately wash contacted area thoroughly with soap and water. If irritation persists, get medical attention.

**EYE CONTACT:** Immediately flush eyes with large amounts of water for 15 minutes. Get medical attention if irritation persists.

**INGESTION:** Seek immediate medical attention. Immediately call local poison control center or go to an emergency department. Never give anything by mouth to or induce vomiting in an unconscious or drowsy person.

**NOTES TO PHYSICIAN:** The principal toxic effects of ethylene glycol, when swallowed, are kidney damage and metabolic acidosis. The combination of metabolic acidosis, an osmol gap and oxalate crystals in the urine is evidence of ethylene glycol poisoning.

Pulmonary edema with hypoxemia has been described in a number of patients following poisoning with ethylene glycol. Respiratory support with mechanical ventilation may be required.

There may be cranial nerve involvement in the late stages of toxicity from swallowed ethylene glycol. In particular, effects have been reported involving the seventh, eighth, and ninth cranial nerves, presenting with bilateral facial paralysis, diminished hearing and dysphagia.

Ethanol is antidotal and its early administration may block the formation of nephrotoxic metabolites of ethylene glycol in the liver. The objective is to rapidly achieve and maintain a blood ethanol level of approximately 100 mg/dl by giving a loading dose of ethanol followed by a maintenance dose. Intravenous administration of ethanol is the preferred route. Ethanol blood levels should be checked frequently. Hemodialysis may be required.

4-Methyl pyrazole (Fomepizole®), a potent inhibitor of alcohol dehydrogenase, has been used therapeutically to decrease the metabolic consequences of ethylene glycol poisoning. Fomepizole® is easier to use clinically than ethanol, does not cause CNS depression or hypoglycemia and requires less monitoring than ethanol. Additional therapeutic modalities which may decrease the adverse consequences of ethylene glycol metabolism are the administration of both thiamine and pyridoxine. As there are complicated and serious overdoses, we recommend you consult with the toxicologists at your poison control center.

The principal toxic effects of sodium nitrite poisoning are vasodilatation and/or methemoglobinemia. Hypotension with syncope and tachycardia are common findings. Coronary vasospasm due to acute withdrawal may be seen. Paradoxical bradycardia may occur rarely. Coronary ischemia and cerebrovascular disease can occur due to severe hypotension. Immediate life support measures should be provided because of associated hypotension, seizures, and methemoglobinemia-induced anoxia. Immediately contact a poison center or hospital emergency department for treatment advice.

## 5. Firefighting Measures

**EXTINGUISHING MEDIA:** For large fires, use alcohol type or all-purpose foams. For small fires, use water spray, carbon dioxide or dry chemical.

**SPECIAL FIRE FIGHTING PROCEDURES:** Do not spray pool fires directly. Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored.

**UNUSUAL FIRE HAZARDS:** A solid stream of water or foam directed into hot, burning liquid can cause frothing.

**HAZARDOUS COMBUSTION PRODUCTS:** Burning may produce carbon monoxide and carbon dioxide.

## 6: Accidental Release Measures

Wear appropriate protective clothing and equipment (See Section 8). Collect with absorbent material and place in appropriate, labeled container for disposal or, if permitted flush spill area with water.

## 7. Handling and Storage

DANGER: Harmful or Fatal if Swallowed

Do not drink antifreeze or solution.  
Avoid eye and prolonged or repeated skin contact.  
Avoid breathing vapors or mists.  
Wash exposed skin thoroughly with soap and water after use.  
Do not store in opened or unlabeled containers.  
Keep container away from open flames and excessive heat.  
Do not reuse empty containers unless properly cleaned.  
Empty containers retain product residue and may be dangerous.  
Do not cut, weld, drill, etc. containers, even empty.

NFPA CLASSIFICATION: Not Applicable

Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without any obvious ignition sources. Published "autoignition" or "ignition" temperatures cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Use of this product in elevated temperature applications should be thoroughly evaluated to assure safe operating conditions.

## 8. Exposure Controls / Personal Protection

### EXPOSURE LIMITS

CHEMICAL	EXPOSURE LIMIT
Ethylene Glycol (as aerosol)	100 mg/m <sup>3</sup> Ceiling ACGIH TLV
Diethylene Glycol	None Established
Sodium Nitrite	None Established

VENTILATION: Use general ventilation or local exhaust as required to maintain exposures below the occupational exposure limits.

RESPIRATORY PROTECTION: For operations where the TLV is exceeded a NIOSH approved respirator with organic vapor cartridges and dust/mist prefilters or supplied air respirator is recommended. Equipment selection depends on contaminant type and concentration. Select and use in accordance with 29 CFR 1910.134 and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.

GLOVES: Chemical resistant gloves such as neoprene or PVC where contact is possible.

EYE PROTECTION: Splash-proof goggles.

OTHER PROTECTIVE EQUIPMENT/CLOTHING: Appropriate protective clothing as needed to minimize skin contact.

## 9. Physical and Chemical Properties

APPEARANCE AND ODOR: Clear, green or purple liquid with a characteristic odor. There is no odor threshold data for this product.

pH: Not determined

BOILING POINT (F): Not determined

FREEZING POINT (F): Not determined

SOLUBILITY IN WATER: 100%

PERCENT VOLATILE: 50%

SPECIFIC GRAVITY: Not determined

VAPOR PRESSURE: < 0.06 mmHg @ 20°C

VAPOR DENSITY: 2.1

EVAPORATION RATE: Not determined

VISCOSITY: Not determined



COEFFICIENT OF WATER/OIL DISTRIBUTION: Not determined  
FLASH POINT: Greater than 241°F TCC      AUTOIGNITION TEMPERATURE: 748°F (estimated)  
FLAMMABILITY LIMITS: LEL: 3.2% (ethylene glycol)      UEL: 15.3% (ethylene glycol)

## 10. Stability and Reactivity

STABILITY: Stable  
CONDITIONS TO AVOID: None  
INCOMPATIBILITY: Normally unreactive, however, avoid strong bases at high temperatures, strong acids, strong oxidizing agents, and materials reactive with hydroxyl compounds.  
DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide.  
HAZARDOUS POLYMERIZATION: Will not occur.

## 11. Toxicological Information

### POTENTIAL HEALTH EFFECTS:

#### ACUTE HAZARDS:

**INHALATION:** May cause irritation of the nose and throat with headache, particularly from mists. High vapor concentrations caused, for example, by heating the material in an enclosed and poorly ventilated workplace, may produce nausea, vomiting, headache, dizziness and irregular eye movements.

**SKIN CONTACT:** No evidence of adverse effects from available information.

**EYE CONTACT:** Liquid, vapors or mist may cause discomfort in the eye with persistent conjunctivitis, seen as slight excess redness or conjunctiva. Serious corneal injury is not anticipated.

**INGESTION:** May cause abdominal discomfort or pain, nausea, vomiting, dizziness, drowsiness, malaise, blurring of vision, irritability, back pain, decrease in urine output, kidney failure, and central nervous system effects, including irregular eye movements, convulsions and coma. Cardiac failure and pulmonary edema may develop. Severe kidney damage which may be fatal may follow the swallowing of ethylene glycol. A few reports have been published describing the development of weakness of the facial muscles, diminishing hearing, and difficulty with swallowing, during the late stages of severe poisoning. This product contains less than 0.5% sodium nitrite. Swallowing sodium nitrite causes the formation of methemoglobin in the blood which may result in cyanosis, lowering of blood pressure, rapid heartbeat and severe headache. Doses as low as 14 mg/kg have been reported to cause toxic effects.

**CHRONIC EFFECTS:** Prolonged or repeated inhalation exposure may produce signs of central nervous system involvement, particularly dizziness and jerking eye movements. Prolonged or repeated skin contact may cause skin sensitization and an associated dermatitis in some individuals. Ethylene glycol has been found to cause birth defects in laboratory animals. The significance of this finding to humans has not been determined.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** The available toxicological information and knowledge of the physical and chemical properties of the material suggest that overexposure is unlikely to aggravate existing medical conditions.

**CARCINOGEN:** None of the components of these products is listed as a carcinogen or suspected carcinogen by IARC, NTP, ACGIH, or OSHA.

#### Acute Toxicity Values:

Ethylene Glycol: LD50 Oral Rat: 4700 mg/kg; LD50 Skin Rabbit: 9530 mg/kg

Diethylene Glycol: LD50 Oral Rat: 12,565 mg/kg; LD50 Skin Rabbit: 11,890 mg/kg

Sodium Nitrite: LD50 Oral Rat: 180 mg/kg; LC50 Inhalation Rat: 5.5 mg/m<sup>3</sup>/4 hr.

**SIGNIFICANT LABORATORY DATA WITH POSSIBLE RELEVANCE TO HUMAN HEALTH:**

Ethylene glycol has been shown to produce dose-related teratogenic effects in rats and mice when given by gavage or in drinking water at high concentrations or doses. Also, in a preliminary study to assess the effects of exposure of pregnant rats and mice to aerosols at concentrations 150, 1,000 and 2,500 mg/m<sup>3</sup> for 6 hours a day throughout the period of organogenesis, teratogenic effects were produced at the highest concentrations, but only in mice. The conditions of these latter experiments did not allow a conclusion as to whether the developmental toxicity was mediated by inhalation of aerosol, percutaneous absorption of ethylene glycol from contaminated skin, or swallowing of ethylene glycol as a result of grooming the wetted coat. In a further study, comparing effects from high aerosol concentration by whole-body or nose-only exposure, it was shown that nose-only exposure resulted in maternal toxicity (1,000 and 2,500 mg/m<sup>3</sup>) and developmental toxicity in with minimal evidence of teratogenicity (2,500 mg/m<sup>3</sup>). The no-effects concentration (based on maternal toxicity) was 500 mg/m<sup>3</sup>. In a further study in mice, no teratogenic effects could be produced when ethylene glycol was applied to the skin of pregnant mice over the period of organogenesis. The above observations suggest that ethylene glycol is to be regarded as an animal teratogen; there is currently no available information to suggest that ethylene glycol caused birth defects in humans. Cutaneous application of ethylene glycol is ineffective in producing developmental toxicity; exposure to high aerosol concentration is only minimally effective in producing developmental toxicity; the major route for producing developmental toxicity is perorally.

Two chronic feeding studies, using rats and mice, have not produced any evidence that ethylene glycol causes dose-related increases in tumor incidence or a different pattern of tumors compared with untreated controls. The absence of carcinogenic potential for ethylene glycol has been supported by numerous invitro genotoxicity studies showing that it does not produce mutagenic or clastogenic effects.

**12. Ecological Information**

Ethylene Glycol: LC50 Goldfish: 5,000 mg/L/24 hr. at 20 C static conditions.  
Toxicity threshold (cell multiplication inhibition test): Bacterial (*Pseudomonas putida*): 10,000 mg/l;  
Protozoa (*Entosiphon sulcatum* and *Uronema parduczi*; *Chatton-Lwoff*) : >10,000 mg/l; Algae (*Microcystis aeruginosa*): 2,000 mg/l; Green algae (*Scenedesmus quadricauda*): >10,000 mg/l

**13. Disposal Considerations**

Dispose of product in accordance with all local, state/provincial and federal regulations.

**14. Transport Information**

U.S. DOT HAZARD CLASSIFICATION: Not Regulated (unless package contains a reportable quantity)

Note: IF A SHIPMENT OF A REPORTABLE QUANTITY (10,000 LBS/1076 GAL) IN A SINGLE PACKAGE IS INVOLVED, THE FOLLOWING INFORMATION APPLIES:

PROPER SHIPPING NAME: RQ, Environmentally hazardous substance, liquid, n.o.s. (Ethylene glycol)

UN NUMBER: UN3082

PACKING GROUP: III

LABELS REQUIRED: Class 9

DOT MARINE POLLUTANTS: This product does not contain Marine Pollutants as defined in 49 CFR 171.8.

IMDG CODE SHIPPING CLASSIFICATION: Not Regulated

CANADIAN TDG CLASSIFICATION: Not Regulated

**15. Regulatory Information**

EPA SARA 311/312 HAZARD CLASSIFICATION: Acute health, chronic health

EPA SARA 313: This Product Contains the Following Chemicals Subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372):

Ethylene Glycol	107-21-1	47-50%
-----------------	----------	--------

PROTECTION OF STRATOSPHERIC OZONE: This product is not known to contain or to have been manufactured with ozone depleting substances as defined in 40 CFR Part 82, Appendix A to Subpart A.


CERCLA SECTION 103: Spills of this product over the RQ (reportable quantity) must be reported to the National Response Center. The RQ for this product, based on the RQ for Ethylene Glycol (50% maximum) of 5,000 lbs., is 10,000 lbs. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

CALIFORNIA PROPOSITION 65: The normal consumer use of this product does not result in exposures to chemicals known to the State of California to cause Cancer and/or Reproductive Harm above the significant risk level for carcinogens or the maximum allowable dose levels for reproductive toxins. Therefore, no warnings are required for consumer packages. Industrial or other occupational use of this product at higher frequency and using larger quantities of this product may result in exposures exceeding these levels and are labeled accordingly.

EPA TSCA INVENTORY: All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

CANADIAN ENVIRONMENTAL PROTECTION ACT: All of the ingredients are listed on the Canadian Domestic Substances List.

CANADIAN WHMIS CLASSIFICATION: Class D - Division 2 - Subdivision A - (A very toxic material causing other toxic effects)



CANADIAN WHMIS HAZARD SYMBOLS:

This SDS has been prepared according to the criteria of the Controlled Products Regulation (CPR) and the SDS contains all of the information required by the CPR.

AUSTRALIA: One of the ingredients of this product is not listed on the Australian Inventory of Chemical Substances.

JAPAN: One of the ingredients of this product is not listed on the Japanese Existing and New Chemical Substances (MITI) List. For formulas YA2792-P50, YA2792-P50-B.

KOREA: One of the ingredients of this product is not listed on the Korean Existing Chemicals List (KECL).

CHINA. One of the ingredients of this product is not listed on the Inventory of Existing Chemical Substances in China (IECSC).

PHILIPPINES One of the ingredients of this product is not listed on the Philippines Inventory of Chemicals and Chemical Substances (PICCS).

<b>16. Other Information</b>
------------------------------

NFPA RATING (NFPA 704) - FIRE: 1      HEALTH: 2      REACTIVITY: 0

REVISION SUMMARY: New SDS.

This SDS is directed to professional users and bulk handlers of the product. Consumer products are labeled in accordance with Federal Hazardous Substances Act regulations.

While Prestone Products Corporation believes that the data contained herein are factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the data are not to be taken as a warranty or representation for which Prestone Products Corporation assumes legal responsibility. They are offered solely for your consideration, investigation and verification. Any use of these data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

If more information is needed, please contact:      Prestone Products Corporation  
69 Eagle Road  
Danbury, CT 06810  
(800) 890-2075



**SAFETY DATA SHEET**

**1. Product And Company Identification**

SDS ID: SDS672  
 PRODUCT NAME: Prestone® Extended Life Heavy Duty Antifreeze/Coolant (Yellow OAT) Pre-diluted 50%  
 PRODUCT NUMBER: AFC12100/F, AFC12100-55/F, AFC12100-1KL/F, 74815, 74097/F, 74352  
 FORMULA NUMBER: YA-993-P50

**MANUFACTURER:**  
 Prestone Products Corporation  
 Danbury, CT 06810-5109

**CANADIAN OFFICE:**  
 FRAM Group (Canada), Inc.  
 Mississauga, Ontario L5L 3S6

**MEDICAL EMERGENCIES AND ALL OTHER INFORMATION PHONE NUMBER:**

(800)890-2075 (in the US)  
 (800)668-9349 (in Canada)

**TRANSPORTATION EMERGENCY PHONE NUMBER (Chemical Spills and Transport Accidents only):**

CHEMTREC 1-800-424-9300 (in the US)  
 CANUTEC (613)996-6666 (in Canada)

SDS DATE OF PREPARATION/REVISION: 04/17/14

PRODUCT USE: Automobile Antifreeze – consumer product  
 RESTRICTIONS ON USE: None identified

**2. Hazards Identification**

**GHS/HAZCOM 2012 Classification:**

Health	Physical
Acute Toxicity Category 4 Specific Target Organ Toxicity – repeated exposure Category 2 Reproductive Toxicity Category 2	Not Hazardous

**Label Elements**



**WARNING!**

H302 Harmful if swallowed.  
 H361d Suspected of damaging the unborn child.  
 H373 May cause damage to kidneys through prolonged or repeated exposure.

**Prevention:**

P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P260 Do not breathe mist or vapors.  
 P264 Wash exposed skin thoroughly after handling.  
 P270 Do not eat, drink, or smoke when using this product.  
 P281 Use personal protective equipment as required.



**Response:**

P301 + P312 IF SWALLOWED: Call a POISON CENTER or physician if you feel unwell.

P330 Rinse mouth.

P308 + P313 IF exposed or concerned: Get medical advice.

**Disposal:**

P405 Store locked up.

P501 Dispose of contents and container in accordance with local and national regulations.

**3. Composition/Information on Ingredients**

Component	CAS No.	Amount
Ethylene Glycol	107-21-1	45-55
Water	7732-18-5	45-55
2-Ethyl Hexanoic Acid, Sodium Salt	19766-89-3	1-5
Diethylene Glycol	111-46-6	0-5

**The exact concentrations are a trade secret.**

**4. First Aid Measures**

**INHALATION:** Remove the victim to fresh air. If breathing has stopped administer artificial respiration. If breathing is difficult, have medical personnel administer oxygen. Get medical attention.

**SKIN CONTACT:** Remove contaminated clothing. Immediately wash contacted area thoroughly with soap and water. If irritation persists, get medical attention.

**EYE CONTACT:** Immediately flush eyes with large amounts of water for 15 minutes. Get medical attention if irritation persists.

**INGESTION:** Seek immediate medical attention. Immediately call local poison control center or go to an emergency department. Never give anything by mouth to or induce vomiting in an unconscious or drowsy person.

**MOST IMPORTANT SYMPTOMS:** May cause eye irritation. Inhalation of mists may cause nose and throat irritation and nervous system effects. Ingestion may cause abdominal discomfort or pain, nausea, vomiting, dizziness, drowsiness, malaise, blurring of vision, irritability, back pain, decrease in urine output, kidney failure, and central nervous system effects.

**INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT, IF NEEDED:** Seek immediate medical attention for large ingestions.

**NOTES TO PHYSICIAN:** The principal toxic effects of ethylene glycol, when swallowed, are kidney damage and metabolic acidosis. The combination of metabolic acidosis, an osmol gap and oxalate crystals in the urine is evidence of ethylene glycol poisoning. Pulmonary edema with hypoxemia has been described in a number of patients following poisoning with ethylene glycol. Respiratory support with mechanical ventilation may be required. There may be cranial nerve involvement in the late stages of toxicity from swallowed ethylene glycol. In particular, effects have been reported involving the seventh, eighth, and ninth cranial nerves, presenting with bilateral facial paralysis, diminished hearing and dysphagia.

Ethanol is antidotal and its early administration may block the formation of nephrotoxic metabolites of ethylene glycol in the liver. The objective is to rapidly achieve and maintain a blood ethanol level of approximately 100 mg/dl by giving a loading dose of ethanol followed by a maintenance dose. Intravenous administration of ethanol is the preferred route. Ethanol blood levels should be checked frequently. Hemodialysis may be required. 4-Methyl pyrazole (Fomepizole®), a potent inhibitor of alcohol dehydrogenase, has been used therapeutically to decrease the metabolic consequences of ethylene glycol poisoning.



Fomepizole® is easier to use clinically than ethanol, does not cause CNS depression or hypoglycemia and requires less monitoring than ethanol. Additional therapeutic modalities which may decrease the adverse consequences of ethylene glycol metabolism are the administration of both thiamine and pyridoxine. As there are complicated and serious overdoses, we recommend you consult with the toxicologists at your poison control center.

**5. Firefighting Measures**

**SUITABLE EXTINGUISHING MEDIA:** For large fires, use alcohol type or all-purpose foams. For small fires, use water spray, carbon dioxide or dry chemical.

**SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:** A solid stream of water or foam directed into hot, burning liquid can cause frothing. Burning may produce carbon monoxide and carbon dioxide.

**SPECIAL FIRE FIGHTING PROCEDURES:** Do not spray pool fires directly. Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored.

**6: Accidental Release Measures**

**PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:** Wear appropriate protective clothing and equipment (See Section 8).

**METHODS AND MATERIALS FOR CONTAINMENT/CLEANUP:** Collect with absorbent material and place in appropriate, labeled container for disposal or, if permitted flush spill area with water.

**7. Handling and Storage**

**PRECAUTIONS FOR SAFE HANDLING:**

Harmful or Fatal if Swallowed. Do not drink antifreeze or solution. Avoid eye and prolonged or repeated skin contact. Avoid breathing vapors or mists. Wash exposed skin thoroughly with soap and water after use. Do not store in opened or unlabeled containers. Keep container away from open flames and excessive heat. Do not reuse empty containers unless properly cleaned. Empty containers retain product residue and may be dangerous. Do not cut, weld, drill, etc. containers, even empty.

Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without any obvious ignition sources. Published "autoignition" or "ignition" temperatures cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Use of this product in elevated temperature applications should be thoroughly evaluated to assure safe operating conditions.

**CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:** Store away from excessive heat and oxidizers.

**NFPA CLASSIFICATION:** IIIB (May qualify for the following consumer quantity exemption: Consumer products that contain not more than 50 percent by volume of water-miscible flammable or combustible liquids, with the remainder of the product consisting of components that do not burn and where packaged in individual containers that do not exceed 1.3 gal (5 L) capacity.)

**8. Exposure Controls / Personal Protection**

**EXPOSURE GUIDELINES**



**SDS 672**  
**PRESTONE® EXTENDED LIFE HEAVY DUTY**  
**ANTIFREEZE/COOLANT (YELLOW OAT) PRE-DILUTED 50%**  
**Date Prepared: 04/17/2014**

CHEMICAL	EXPOSURE LIMIT
Ethylene Glycol (as aerosol)	100 mg/m <sup>3</sup> Ceiling ACGIH TLV
Diethylene Glycol	10 mg/m <sup>3</sup> TWA AIHA WEELs
2-Ethyl Hexanoic Acid	None Established

APPROPRIATE ENGINEERING CONTROLS: Use general ventilation or local exhaust as required to maintain exposures below the occupational exposure limits.

**PERSONAL PROTECTIVE EQUIPMENT**

RESPIRATORY PROTECTION: For operations where the TLV is exceeded a NIOSH approved respirator with organic vapor cartridges and dust/mist prefilters or supplied air respirator is recommended. Equipment selection depends on contaminant type and concentration. Select and use in accordance with 29 CFR 1910.134 and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.

GLOVES: Chemical resistant gloves such as neoprene or PVC where contact is possible.

EYE PROTECTION: Splash-proof goggles.

OTHER PROTECTIVE EQUIPMENT/CLOTHING: Appropriate protective clothing as needed to minimize skin contact.

**9. Physical and Chemical Properties**

APPEARANCE:	Yellow liquid	ODOR:	Characteristic odor
ODOR THRESHOLD:	Not determined	pH:	8.7
MELTING/FREEZING POINT:	-34°F (-36°C)	BOILING POINT/RANGE:	226°F (108°C)
FLASH POINT:	>215°F (>101.6°C) None through boiling. SETA Flash CC	EVAPORATION RATE:	Not determined
FLAMMABILITY (SOLID, GAS)	Not Applicable	FLAMMABILITY LIMITS:	LEL: Not determined UEL: Not determined
VAPOR PRESSURE:	Not determined	VAPOR DENSITY:	Not determined
RELATIVE DENSITY:	1.06 – 1.07	SOLUBILITIES	Water: 100%
PARTITION COEFFICIENT (n-octanol/water)	Not determined	AUTOIGNITION TEMPERATURE:	Not determined
DECOMPOSITION TEMPERATURE:	Not determined	VISCOSITY:	Not determined

**10. Stability and Reactivity**

REACTIVITY: Normally unreactive

CHEMICAL STABILITY: Stable

POSSIBILITY OF HAZARDOUS REACTIONS: Reaction with strong oxidizers will generate heat.

CONDITIONS TO AVOID: None known

INCOMPATIBLE MATERIALS: Avoid strong bases at high temperatures, strong acids, strong oxidizing agents, and materials reactive with hydroxyl compounds.





HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide.

<b>11. Toxicological Information</b>
--------------------------------------

**POTENTIAL HEALTH EFFECTS:**

**ACUTE HAZARDS:**

**INHALATION:** May cause irritation of the nose and throat with headache, particularly from mists. High vapor concentrations caused, for example, by heating the material in an enclosed and poorly ventilated workplace, may produce nausea, vomiting, headache, dizziness and irregular eye movements.

**SKIN CONTACT:** No evidence of adverse effects from available information.

**EYE CONTACT:** Liquid, vapors or mist may cause discomfort in the eye with persistent conjunctivitis, seen as slight excess redness or conjunctiva. Serious corneal injury is not anticipated.

**INGESTION:** May cause abdominal discomfort or pain, nausea, vomiting, dizziness, drowsiness, malaise, blurring of vision, irritability, back pain, decrease in urine output, kidney failure, and central nervous system effects, including irregular eye movements, convulsions and coma. Cardiac failure and pulmonary edema may develop. Severe kidney damage which may be fatal may follow the swallowing of ethylene glycol. A few reports have been published describing the development of weakness of the facial muscles, diminishing hearing, and difficulty with swallowing, during the late stages of severe poisoning.

**CHRONIC EFFECTS:** Prolonged or repeated inhalation exposure may produce signs of central nervous system involvement, particularly dizziness and jerking eye movements. Prolonged or repeated skin contact may cause skin sensitization and an associated dermatitis in some individuals. Ethylene glycol has been found to cause birth defects in laboratory animals. The significance of this finding to humans has not been determined. 2-Ethyl Hexanoic Acid, Sodium Salt is suspected of causing developmental effects based on animal data.

**CARCINOGENICITY LISTING:** None of the components of these products is listed as a carcinogen or suspected carcinogen by IARC, NTP, ACGIH, or OSHA.

**ACUTE TOXICITY VALUES:**

Ethylene Glycol:           LD50 Oral Rat: 4700 mg/kg  
                                  LD50 Skin Rabbit: 9530 mg/kg

Diethylene Glycol:       LD50 Oral Rat: 12,565 mg/kg  
                                  LD50 Skin Rabbit: 11,890 mg/kg

**SIGNIFICANT LABORATORY DATA WITH POSSIBLE RELEVANCE TO HUMAN HEALTH:**

Ethylene glycol has been shown to produce dose-related teratogenic effects in rats and mice when given by gavage or in drinking water at high concentrations or doses. Also, in a preliminary study to assess the effects of exposure of pregnant rats and mice to aerosols at concentrations 150, 1,000 and 2,500 mg/m<sup>3</sup> for 6 hours a day throughout the period of organogenesis, teratogenic effects were produced at the highest concentrations, but only in mice. The conditions of these latter experiments did not allow a conclusion as to whether the developmental toxicity was mediated by inhalation of aerosol, percutaneous absorption of ethylene glycol from contaminated skin, or swallowing of ethylene glycol as a result of grooming the wetted coat. In a further study, comparing effects from high aerosol concentration by whole-body or nose-only exposure, it was shown that nose-only exposure resulted in maternal toxicity (1,000 and 2,500 mg/m<sup>3</sup>) and developmental toxicity in with minimal evidence of teratogenicity (2,500 mg/m<sup>3</sup>). The no-effects concentration (based on maternal toxicity) was 500 mg/m<sup>3</sup>. In a further study in mice, no teratogenic effects could be produced when ethylene glycol was applied to the skin of pregnant mice over the period of organogenesis. The above observations suggest that ethylene glycol is to be regarded as an animal teratogen; there is currently no available information to suggest that ethylene glycol caused birth defects in humans.



**SDS 672**  
**PRESTONE® EXTENDED LIFE HEAVY DUTY**  
**ANTIFREEZE/COOLANT (YELLOW OAT) PRE-DILUTED 50%**  
**Date Prepared: 04/17/2014**

Cutaneous application of ethylene glycol is ineffective in producing developmental toxicity; exposure to high aerosol concentration is only minimally effective in producing developmental toxicity; the major route for producing developmental toxicity is perorally.

Two chronic feeding studies, using rats and mice, have not produced any evidence that ethylene glycol causes dose-related increases in tumor incidence or a different pattern of tumors compared with untreated controls. The absence of carcinogenic potential for ethylene glycol has been supported by numerous invitro genotoxicity studies showing that it does not produce mutagenic or clastogenic effects.

In a study of Wistar rats, adverse developmental results were reported at a dose of 100 mg / kg of body weight for 2-Ethyl Hexanoic Acid, Sodium Salt.

This product contains less than 0.2% tolytriazole which has demonstrated mutagenic activity in a bacterial test system. A correlation has been established between mutagenic activity and carcinogenic activity for many chemicals. Tolytriazole has not been identified as a carcinogen or probable carcinogen by NTP, IARC, ACGIH, or OSHA.

**12. Ecological Information**

**ECOTOXICITY:**

- Ethylene Glycol: LC50 Fathead Minnow <10,000 mg/L/96 hr.
- EC50 Daphnia Magna 100,000 mg/L/48 hr
- Bacterial (*Pseudomonas putida*): 10,000 mg/l
- Protozoa (*Entosiphon sulcatum* and *Uronema parduczi*; Chatton-Lwoff): >10,000 mg/l
- Algae (*Microcystis aeruginosa*): 2,000 mg/l
- Green algae (*Scenedesmus quadricauda*): >10,000 mg/l
- Diethylene Glycol: LC50 western mosquitofish >32,000 mg/L/96 hr

**PERSISTENCE AND DEGRADABILITY:**

- Ethylene Glycol is readily biodegradable (97-100% in 2-12 days).
- Diethylene glycol is readily biodegradable (>70% in 19days).

**BIOACCUMULATIVE POTENTIAL:**

- Ethylene glycol: A BCF of 10, reported for ethylene glycol in fish, Golden ide (*Leuciscus idus melanotus*), after 3 days of exposure suggests the potential for bio concentration in aquatic organisms is low.
- Diethylene glycol: An estimated BCF of 3 suggests the potential for bio concentration in aquatic organisms is low.

**MOBILITY IN SOIL:** Ethylene glycol and diethylene glycol are highly mobile in soil.

**OTHER ADVERSE EFFECTS:** None known

**13. Disposal Considerations**

Dispose of product in accordance with all local, state/provincial and federal regulations.

**14. Transport Information**

U.S. DOT HAZARD CLASSIFICATION: Not regulated (unless package contains a reportable quantity)

Note: IF A SHIPMENT OF A REPORTABLE QUANTITY (9,090 LBS/1,018 GAL.) IN A SINGLE PACKAGE IS INVOLVED, THE FOLLOWING INFORMATION APPLIES:

- PROPER SHIPPING NAME: RQ, Environmentally hazardous substance, liquid, n.o.s. (Ethylene glycol)
- UN NUMBER: UN3082
- PACKING GROUP: III
- LABELS REQUIRED: Class 9



DOT MARINE POLLUTANTS: This product does not contain Marine Pollutants as defined in 49 CFR 171.8.

IMDG CODE SHIPPING CLASSIFICATION: Not Regulated

CANADIAN TDG CLASSIFICATION: Not Regulated

<b>15. Regulatory Information</b>
-----------------------------------

CERCLA SECTION 103: Spills of this product over the RQ (reportable quantity) must be reported to the National Response Center. The RQ for this product, based on the RQ for Ethylene Glycol (55% maximum) of 5,000 lbs., is 9,090 lbs. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

EPA SARA 311/312 HAZARD CLASSIFICATION: Acute health, chronic health

EPA SARA 313: This Product Contains the Following Chemicals Subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372):

Ethylene Glycol	107-21-1	45-55%
-----------------	----------	--------

PROTECTION OF STRATOSPHERIC OZONE: This product is not known to contain or to have been manufactured with ozone depleting substances as defined in 40 CFR Part 82, Appendix A to Subpart A.

CALIFORNIA PROPOSITION 65: The normal consumer use of this product does not result in exposures to chemicals known to the State of California to cause Cancer and/or Reproductive Harm above the significant risk level for carcinogens or the maximum allowable dose levels for reproductive toxins. Therefore, no warnings are required for consumer packages. Industrial or other occupational use of this product at higher frequency and using larger quantities of this product may result in exposures exceeding these levels and are labeled accordingly.

EPA TSCA INVENTORY: All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

CANADIAN WHMIS CLASSIFICATION: Class D - Division 2 - Subdivision A - (A very toxic material causing other toxic effects)



CANADIAN WHMIS HAZARD SYMBOLS:

This SDS has been prepared according to the criteria of the Controlled Products Regulation (CPR) and the SDS contains all of the information required by the CPR.

EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES (EINECS): All of the ingredients are listed on the EINECS inventory.

AUSTRALIA: All of the components of this material are on the Australian Inventory of Chemical Substances (AICS).

JAPAN: All of the components of this material are listed on the Japanese Existing and New Chemical Substances (METI) List.

CHINA: All of the ingredients of this product are listed on the Inventory of Existing Chemical Substances in China (IECSC)

KOREA: All of the components of this material are listed on the Korean Existing Chemicals List (KECL).

PHILIPPINES: All of the components of this material are listed on the Philippines Inventory of Chemicals and Chemical Substances (PICCS).



**SDS 672**  
**PRESTONE® EXTENDED LIFE HEAVY DUTY**  
**ANTIFREEZE/COOLANT (YELLOW OAT) PRE-DILUTED 50%**  
**Date Prepared: 04/17/2014**

NEW ZEALAND: All of the components of this material are listed on the New Zealand Inventory of Chemicals. (NZIoC)

<b>16. Other Information</b>
------------------------------

NFPA RATING - FIRE: 1      HEALTH: 2      INSTABILITY: 0

REVISION SUMMARY: New SDS

SDS Date of Preparation/Revision: April 17, 2014

This SDS is directed to professional users and bulk handlers of the product. Consumer products are labeled in accordance with Federal Hazardous Substances Act regulations.

While Prestone Products Corporation believes that the data contained herein are factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the data are not to be taken as a warranty or representation for which Prestone Products Corporation assumes legal responsibility. They are offered solely for your consideration, investigation and verification. Any use of these data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

If more information is needed, please contact:      Prestone Products Corporation  
69 Eagle Road  
Danbury CT 06810  
(800) 890-2075



**SAFETY DATA SHEET**

**1. Product And Company Identification**

SDS ID: SDS787  
 PRODUCT NAME: Prestone ® Command Heavy Duty CorGuard Antifreeze/Coolant  
 PRODUCT NUMBER: AFC13000/F, AFC13000-55, AFC13000-1KL, 74100, AFC13000-55/F, AFC13000-1KL/F, AFC13000BULK/F, 74100/F, 74100/FC, 74100/FC3, 74100-55/F, 74100-1KL/F  
 FORMULA NUMBER: YA-997

<b>MANUFACTURER:</b> Prestone Products Corporation 69 Eagle Rd. Danbury, CT 06810	<b>CANADIAN OFFICE:</b> Prestone Canada Inc. 33 MacIntosh Blvd. Concord, ON L4K 4L5	<b>MEXICO OFFICE:</b> ASG Operations Mexico S. de R.L. de C.V. Carretera Mexico Cuautitlan, Kilometro 31.5, Nave Industrial 5, Loma Bonita, Cuautitlan, Mexico, 54800
--	--	--

**MEDICAL EMERGENCIES AND ALL OTHER INFORMATION PHONE NUMBER:**

(888)269-0750 (in the US and Canada)  
 01-800-715-4135 (in Mexico)

**TRANSPORTATION EMERGENCY PHONE NUMBER (Chemical Spills and Transport Accidents only):**

CHEMTREC 1-800-424-9300 (in the US and Canada) +1 703 741-5970 (outside the US and Canada)

PRODUCT USE: Automobile Antifreeze – consumer product

RESTRICTIONS ON USE: None identified

**2. Hazards Identification**

**GHS/HAZCOM 2012 Classification:**

Health	Physical
Acute Toxicity Category 4 Specific Target Organ Toxicity – Repeated Exposure Category 2	Not Hazardous

**Label Elements**



**WARNING!**

H302 Harmful if swallowed.

H373 May cause damage to kidneys through prolonged or repeated exposure.

**Prevention:**

P260 Do not breathe mist or vapors.

P264 Wash exposed skin thoroughly after handling.

P270 Do not eat, drink, or smoke when using this product.

P280 Wear protective gloves and eye protection.

**Response:**

P301 + P312 IF SWALLOWED: Call a POISON CENTER or physician if you feel unwell.

P330 Rinse mouth.

**Disposal:**



P501 Dispose of contents and container in accordance with local and national regulations.

### 3. Composition/Information On Ingredients

Component	CAS No.	Amount
Ethylene Glycol	107-21-1	80-100%
Diethylene Glycol	111-46-6	0-5%

The exact concentrations are a trade secret.

### 4. First Aid Measures

**INHALATION:** Remove the victim to fresh air. If breathing has stopped administer artificial respiration. If breathing is difficult, have medical personnel administer oxygen. Get medical attention.

**SKIN CONTACT:** Remove contaminated clothing. Immediately wash contacted area thoroughly with soap and water. If irritation persists, get medical attention.

**EYE CONTACT:** Immediately flush eyes with large amounts of water for 15 minutes. Get medical attention if irritation persists.

**INGESTION:** Seek immediate medical attention. Immediately call local poison control center or go to an emergency department. Never give anything by mouth to or induce vomiting in an unconscious or drowsy person.

**MOST IMPORTANT SYMPTOMS:** May cause eye irritation. Inhalation of mists may cause nose and throat irritation and nervous system effects. Ingestion may cause abdominal discomfort or pain, nausea, vomiting, dizziness, drowsiness, malaise, blurring of vision, irritability, back pain, decrease in urine output, kidney failure, and central nervous system effects.

**INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT, IF NEEDED:** Seek immediate medical attention for large ingestions.

**NOTES TO PHYSICIAN:** The principal toxic effects of ethylene glycol, when swallowed, are kidney damage and metabolic acidosis. The combination of metabolic acidosis, an osmol gap and oxalate crystals in the urine is evidence of ethylene glycol poisoning. Pulmonary edema with hypoxemia has been described in a number of patients following poisoning with ethylene glycol. Respiratory support with mechanical ventilation may be required. There may be cranial nerve involvement in the late stages of toxicity from swallowed ethylene glycol. In particular, effects have been reported involving the seventh, eighth, and ninth cranial nerves, presenting with bilateral facial paralysis, diminished hearing and dysphagia.

Ethanol is antidotal and its early administration may block the formation of nephrotoxic metabolites of ethylene glycol in the liver. The objective is to rapidly achieve and maintain a blood ethanol level of approximately 100 mg/dl by giving a loading dose of ethanol followed by a maintenance dose. Intravenous administration of ethanol is the preferred route. Ethanol blood levels should be checked frequently. Hemodialysis may be required. 4-Methyl pyrazole (Fomepizole®), a potent inhibitor of alcohol dehydrogenase, has been used therapeutically to decrease the metabolic consequences of ethylene glycol poisoning. Fomepizole® is easier to use clinically than ethanol, does not cause CNS depression or hypoglycemia and requires less monitoring than ethanol. Additional therapeutic modalities which may decrease the adverse consequences of ethylene glycol metabolism are the administration of both thiamine and pyridoxine. As there are complicated and serious overdoses, we recommend you consult with the toxicologists at your poison control center.

### 5. Firefighting Measures

**SUITABLE EXTINGUISHING MEDIA:** For large fires, use alcohol type or all-purpose foams. For small fires, use water spray, carbon dioxide or dry chemical.



**SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:** A solid stream of water or foam directed into hot, burning liquid can cause frothing. Burning may produce carbon monoxide and carbon dioxide.

**SPECIAL FIRE FIGHTING PROCEDURES:** Do not spray pool fires directly. Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored.

**6: Accidental Release Measures**

**PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:** Wear appropriate protective clothing and equipment (See Section 8).

**METHODS AND MATERIALS FOR CONTAINMENT/CLEANUP:** Collect with absorbent material and place in appropriate, labeled container for disposal or, if permitted flush spill area with water.

**7. Handling and Storage**

**PRECAUTIONS FOR SAFE HANDLING:**

Harmful or Fatal if Swallowed. Do not drink antifreeze or solution. Avoid eye and prolonged or repeated skin contact. Avoid breathing vapors or mists. Wash exposed skin thoroughly with soap and water after use. Do not store in opened or unlabeled containers. Keep container away from open flames and excessive heat. Do not reuse empty containers unless properly cleaned. Empty containers retain product residue and may be dangerous. Do not cut, weld, drill, etc. containers, even empty.

Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without any obvious ignition sources. Published "autoignition" or "ignition" temperatures cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Use of this product in elevated temperature applications should be thoroughly evaluated to assure safe operating conditions.

**CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:** Store away from excessive heat and oxidizers.

**NFPA CLASSIFICATION:** IIIIB

**8. Exposure Controls / Personal Protection**

**EXPOSURE GUIDELINES**

CHEMICAL	EXPOSURE LIMIT
Ethylene Glycol	25 ppm TWA, 50 ppm STEL ACGIH TLV (as vapor) 10 mg/m <sup>3</sup> TWA ACGIH TLV (as inhalable fraction of the aerosol)
Diethylene Glycol	10 mg/m <sup>3</sup> TWA AIHA WEEL

**APPROPRIATE ENGINEERING CONTROLS:** Use general ventilation or local exhaust as required to maintain exposures below the occupational exposure limits.

**PERSONAL PROTECTIVE EQUIPMENT**

**RESPIRATORY PROTECTION:** For operations where the occupational exposure limit is exceeded a NIOSH approved respirator with organic vapor cartridges and dust/mist prefilters or supplied air respirator is recommended. Equipment selection depends on contaminant type and concentration. Select and use in accordance with 29 CFR 1910.134 and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.



GLOVES: Chemical resistant gloves such as neoprene or PVC where contact is possible.

EYE PROTECTION: Splash-proof goggles.

OTHER PROTECTIVE EQUIPMENT/CLOTHING: Appropriate protective clothing as needed to minimize skin contact.

### 9. Physical and Chemical Properties

APPEARANCE:	Clear, red liquid	ODOR:	Characteristic odor
ODOR THRESHOLD:	Not determined	pH:	8.1-8.7
MELTING/FREEZING POINT:	-8°F (-22°C)	BOILING POINT/RANGE:	330°F (166°C)
FLASH POINT:	>215°F (>101.7°C) TCC	EVAPORATION RATE:	Not determined
FLAMMABILITY (SOLID, GAS)	Not Applicable	FLAMMABILITY LIMITS:	LEL: 3.2% (ethylene glycol) UEL: 15.3% (ethylene glycol)
VAPOR PRESSURE:	< 0.1 mmHg @ 20°C	VAPOR DENSITY:	2.1
RELATIVE DENSITY:	1.12	SOLUBILITIES	Water: 100 %
PARTITION COEFFICIENT (n-octanol/water)	Not determined	AUTOIGNITION TEMPERATURE:	748°F (397.8°C) (estimated)
DECOMPOSITION TEMPERATURE:	Not determined	VISCOSITY:	Not determined

### 10. Stability and Reactivity

REACTIVITY: Normally unreactive

CHEMICAL STABILITY: Stable

POSSIBILITY OF HAZARDOUS REACTIONS: Reaction with strong oxidizers will generate heat.

CONDITIONS TO AVOID: None known

INCOMPATIBLE MATERIALS: Avoid strong bases at high temperatures, strong acids, strong oxidizing agents, and materials reactive with hydroxyl compounds.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide.

### 11. Toxicological Information

#### POTENTIAL HEALTH EFFECTS:

##### ACUTE HAZARDS:

INHALATION: May cause irritation of the nose and throat with headache, particularly from mists. High vapor concentrations caused, for example, by heating the material in an enclosed and poorly ventilated workplace, may produce nausea, vomiting, headache, dizziness and irregular eye movements.

SKIN CONTACT: No evidence of adverse effects from available information.

EYE CONTACT: Liquid, vapors or mist may cause discomfort in the eye with persistent conjunctivitis, seen as slight excess redness or conjunctiva. Serious corneal injury is not anticipated.

INGESTION: May cause abdominal discomfort or pain, nausea, vomiting, dizziness, drowsiness, malaise, blurring of vision,





irritability, back pain, decrease in urine output, kidney failure, and central nervous system effects, including irregular eye movements, convulsions and coma. Cardiac failure and pulmonary edema may develop. Severe kidney damage which may be fatal may follow the swallowing of ethylene glycol. A few reports have been published describing the development of weakness of the facial muscles, diminishing hearing, and difficulty with swallowing, during the late stages of severe poisoning.

**CHRONIC EFFECTS:** Prolonged or repeated inhalation exposure may produce signs of central nervous system involvement, particularly dizziness and jerking eye movements. Prolonged or repeated skin contact may cause skin sensitization and an associated dermatitis in some individuals. Ethylene glycol has been found to cause birth defects in laboratory animals. The significance of this finding to humans has not been determined.

**CARCINOGENICITY LISTING:** None of the components of these products is listed as a carcinogen or suspected carcinogen by IARC, NTP, ACGIH or OSHA.

**ACUTE TOXICITY VALUES:**

Ethylene Glycol: LD50 Oral Rat: 4700 mg/kg;  
LD50 Skin Rabbit: 9530 mg/kg

Diethylene Glycol: LD50 Oral Rat: 12,565 mg/kg;  
LD50 Skin Rabbit: 11,890 mg/kg

**SIGNIFICANT LABORATORY DATA WITH POSSIBLE RELEVANCE TO HUMAN HEALTH:** Ethylene glycol has been shown to produce dose-related teratogenic effects in rats and mice when given by gavage or in drinking water at high concentrations or doses. Also, in a preliminary study to assess the effects of exposure of pregnant rats and mice to aerosols at concentrations 150, 1,000 and 2,500 mg/m<sup>3</sup> for 6 hours a day throughout the period of organogenesis, teratogenic effects were produced at the highest concentrations, but only in mice. The conditions of these latter experiments did not allow a conclusion as to whether the developmental toxicity was mediated by inhalation of aerosol, percutaneous absorption of ethylene glycol from contaminated skin, or swallowing of ethylene glycol as a result of grooming the wetted coat. In a further study, comparing effects from high aerosol concentration by whole-body or nose-only exposure, it was shown that nose-only exposure resulted in maternal toxicity (1,000 and 2,500 mg/m<sup>3</sup>) and developmental toxicity in with minimal evidence of teratogenicity (2,500 mg/m<sup>3</sup>). The no-effects concentration (based on maternal toxicity) was 500 mg/m<sup>3</sup>. In a further study in mice, no teratogenic effects could be produced when ethylene glycol was applied to the skin of pregnant mice over the period of organogenesis. The above observations suggest that ethylene glycol is to be regarded as an animal teratogen; there is currently no available information to suggest that ethylene glycol caused birth defects in humans. Cutaneous application of ethylene glycol is ineffective in producing developmental toxicity; exposure to high aerosol concentration is only minimally effective in producing developmental toxicity; the major route for producing developmental toxicity is perorally.

Two chronic feeding studies, using rats and mice, have not produced any evidence that ethylene glycol causes dose-related increases in tumor incidence or a different pattern of tumors compared with untreated controls. The absence of carcinogenic potential for ethylene glycol has been supported by numerous invitro genotoxicity studies showing that it does not produce mutagenic or clastogenic effects.

**12. Ecological Information**

**ECOTOXICITY:**

Ethylene Glycol: LC50 Fathead Minnow <10,000 mg/L/96 hr  
EC50 Daphnia Magna 100,000 mg/L/48 hr  
Bacterial (Pseudomonas putida): 10,000 mg/l  
Protozoa (Entosiphon sulcatum and Uronema parduczi; Chatton-Lwoff): >10,000 mg/l  
Algae (Microcystis aeruginosa): 2,000 mg/l  
Green algae (Scenedesmus quadricauda): >10,000 mg/l

Diethylene Glycol: LC50 western mosquitofish >32,000 mg/L/96 hr

**PERSISTENCE AND DEGRADABILITY:**



Ethylene Glycol is readily biodegradable (97-100% in 2-12 days). Diethylene glycol is readily biodegradable (>70% in 19 days).

**BIOACCUMULATIVE POTENTIAL:**

Ethylene glycol: A BCF of 10, reported for ethylene glycol in fish, Golden ide (*Leuciscus idus melanotus*), after 3 days of exposure suggests the potential for bioconcentration in aquatic organisms is low.

Diethylene glycol: An estimated BCF of 3 suggests the potential for bioconcentration in aquatic organisms is low.

**MOBILITY IN SOIL:** Ethylene glycol and diethylene glycol are highly mobile in soil.

**OTHER ADVERSE EFFECTS:** None known

**13. Disposal Considerations**

Dispose of product in accordance with all local, state/provincial and federal regulations.

**14. Transport Information**

**U.S. DOT HAZARD CLASSIFICATION:** Not Regulated (unless package contains a reportable quantity)

**Note: IF A SHIPMENT OF A REPORTABLE QUANTITY (5,000 LBS/534 GAL) IN A SINGLE PACKAGE IS INVOLVED, THE FOLLOWING INFORMATION APPLIES:**

**PROPER SHIPPING NAME:** RQ, Environmentally hazardous substance, liquid, n.o.s. (Ethylene glycol)

**UN NUMBER:** UN3082

**PACKING GROUP:** III

**LABELS REQUIRED:** Class 9

**DOT MARINE POLLUTANTS:** This product does not contain Marine Pollutants as defined in 49 CFR 171.8.

**IMDG CODE SHIPPING CLASSIFICATION:** Not Regulated

**CANADIAN TDG CLASSIFICATION:** Not Regulated

**15. Regulatory Information**

**EPA SARA 311/312 HAZARD CLASSIFICATION:** Refer to Section 2 for OSHA Hazard Classification.

**EPA SARA 313:** This Product Contains the Following Chemicals Subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372):

Ethylene Glycol	107-21-1	80-100%
-----------------	----------	---------

**PROTECTION OF STRATOSPHERIC OZONE:** This product is not known to contain or to have been manufactured with ozone depleting substances as defined in 40 CFR Part 82, Appendix A to Subpart A.

**CERCLA SECTION 103:** Spills of this product over the RQ (reportable quantity) must be reported to the National Response Center. The RQ for this product, based on the RQ for Ethylene Glycol (100% maximum) of 5,000 lbs., is 5,000 lbs. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

**CALIFORNIA PROPOSITION 65:** This product contains the following chemicals regulated under California Proposition 65:

Ethylene Glycol	107-21-1	80-100%	developmental
-----------------	----------	---------	---------------

**EPA TSCA INVENTORY:** All of the components of this material are listed on the Toxic Substances Control Act (TSCA)



Chemical Substances Inventory.

CANADIAN ENVIRONMENTAL PROTECTION ACT: All of the ingredients are listed on the Canadian Domestic Substances List.

KOREA: All of the ingredients of this product are listed on the Korean Existing Chemical List (KECL).

CHINA. All of the ingredients of this product are listed on the Inventory of Existing Chemical Substances in China (IECSC).

PHILIPPINES: All of the ingredients of this product are listed on the Philippine Inventory of Chemical and Chemical Substance (PICCS)

<b>16. Other Information</b>
------------------------------

NFPA RATING (NFPA 704) - FIRE: 1      HEALTH: 2      REACTIVITY: 0

REVISION SUMMARY: Section 1 Added Product Numbers

SDS Date of Preparation/Revision: June 16, 2019

This SDS is directed to professional users and bulk handlers of the product. Consumer products are labeled in accordance with Federal Hazardous Substances Act regulations.

While Prestone Products Corporation believes that the data contained herein are factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the data are not to be taken as a warranty or representation for which Prestone Products Corporation assumes legal responsibility. They are offered solely for your consideration, investigation and verification. Any use of these data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.



**SAFETY DATA SHEET**

**1. Product And Company Identification**

SDS ID: SDS799  
 PRODUCT NAME: Prestone ® Command Heavy Duty CorGuard 50/50 Antifreeze/Coolant  
 PRODUCT NUMBER: AFC13100/F, AFC13100-55, AFC13100-1KL, 74050, AFC13100-55/F, AFC13100-1KL/F, AFC13100BULK/F, 74050/F, 74050/FC, 74050/FC3, 74050-55/F, 74050-1KL/F  
 FORMULA NUMBER: YA-997-P50

<b>MANUFACTURER:</b> Prestone Products Corporation 69 Eagle Rd. Danbury, CT 06810	<b>CANADIAN OFFICE:</b> Prestone Canada Inc. 33 MacIntosh Blvd. Concord, ON L4K 4L5	<b>MEXICO OFFICE:</b> ASG Operations Mexico S. de R.L. de C.V. Carretera Mexico Cuautitlan, Kilometro 31.5, Nave Industrial 5, Loma Bonita, Cuautitlan, Mexico, 54800
--	--	--

**MEDICAL EMERGENCIES AND ALL OTHER INFORMATION PHONE NUMBER:**

(888)269-0750 (in the US and Canada)  
 01-800-715-4135 (in Mexico)

**TRANSPORTATION EMERGENCY PHONE NUMBER (Chemical Spills and Transport Accidents only):**

CHEMTREC 1-800-424-9300 (in the US and Canada) +1 703 741-5970 (outside the US and Canada)

PRODUCT USE: Automobile Antifreeze – consumer product

RESTRICTIONS ON USE: None identified

**2. Hazards Identification**

**GHS/HAZCOM 2012 Classification:**

Health	Physical
Acute Toxicity Category 4 Specific Target Organ Toxicity – Repeated Exposure Category 2	Not Hazardous

**Label Elements**



**WARNING!**

H302 Harmful if swallowed.

H373 May cause damage to kidneys through prolonged or repeated exposure.

**Prevention:**

P260 Do not breathe mist or vapors.

P264 Wash exposed skin thoroughly after handling.

P270 Do not eat, drink, or smoke when using this product.

P280 Wear protective gloves and eye protection.

**Response:**

P301 + P312 IF SWALLOWED: Call a POISON CENTER or physician if you feel unwell.

P330 Rinse mouth.

**Disposal:**



P501 Dispose of contents and container in accordance with local and national regulations.

### 3. Composition/Information On Ingredients

Component	CAS No.	Amount
Water	7732-18-5	40-60%
Ethylene Glycol	107-21-1	40-60%
Diethylene Glycol	111-46-6	0-5%

**The exact concentrations are a trade secret.**

### 4. First Aid Measures

**INHALATION:** Remove the victim to fresh air. If breathing has stopped administer artificial respiration. If breathing is difficult, have medical personnel administer oxygen. Get medical attention.

**SKIN CONTACT:** Remove contaminated clothing. Immediately wash contacted area thoroughly with soap and water. If irritation persists, get medical attention.

**EYE CONTACT:** Immediately flush eyes with large amounts of water for 15 minutes. Get medical attention if irritation persists.

**INGESTION:** Seek immediate medical attention. Immediately call local poison control center or go to an emergency department. Never give anything by mouth to or induce vomiting in an unconscious or drowsy person.

**MOST IMPORTANT SYMPTOMS:** May cause eye irritation. Inhalation of mists may cause nose and throat irritation and nervous system effects. Ingestion may cause abdominal discomfort or pain, nausea, vomiting, dizziness, drowsiness, malaise, blurring of vision, irritability, back pain, decrease in urine output, kidney failure, and central nervous system effects.

**INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT, IF NEEDED:** Seek immediate medical attention for large ingestions.

**NOTES TO PHYSICIAN:** The principal toxic effects of ethylene glycol, when swallowed, are kidney damage and metabolic acidosis. The combination of metabolic acidosis, an osmol gap and oxalate crystals in the urine is evidence of ethylene glycol poisoning. Pulmonary edema with hypoxemia has been described in a number of patients following poisoning with ethylene glycol. Respiratory support with mechanical ventilation may be required. There may be cranial nerve involvement in the late stages of toxicity from swallowed ethylene glycol. In particular, effects have been reported involving the seventh, eighth, and ninth cranial nerves, presenting with bilateral facial paralysis, diminished hearing and dysphagia.

Ethanol is antidotal and its early administration may block the formation of nephrotoxic metabolites of ethylene glycol in the liver. The objective is to rapidly achieve and maintain a blood ethanol level of approximately 100 mg/dl by giving a loading dose of ethanol followed by a maintenance dose. Intravenous administration of ethanol is the preferred route. Ethanol blood levels should be checked frequently. Hemodialysis may be required. 4-Methyl pyrazole (Fomepizole®), a potent inhibitor of alcohol dehydrogenase, has been used therapeutically to decrease the metabolic consequences of ethylene glycol poisoning. Fomepizole® is easier to use clinically than ethanol, does not cause CNS depression or hypoglycemia and requires less monitoring than ethanol. Additional therapeutic modalities which may decrease the adverse consequences of ethylene glycol metabolism are the administration of both thiamine and pyridoxine. As there are complicated and serious overdoses, we recommend you consult with the toxicologists at your poison control center.

### 5. Firefighting Measures

**SUITABLE EXTINGUISHING MEDIA:** For large fires, use alcohol type or all-purpose foams. For small fires, use water spray, carbon dioxide or dry chemical.



**SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:** A solid stream of water or foam directed into hot, burning liquid can cause frothing. Burning may produce carbon monoxide and carbon dioxide.

**SPECIAL FIRE FIGHTING PROCEDURES:** Do not spray pool fires directly. Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored.

**6: Accidental Release Measures**

**PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:** Wear appropriate protective clothing and equipment (See Section 8).

**METHODS AND MATERIALS FOR CONTAINMENT/CLEANUP:** Collect with absorbent material and place in appropriate, labeled container for disposal or, if permitted flush spill area with water.

**7. Handling and Storage**

**PRECAUTIONS FOR SAFE HANDLING:**

Harmful or Fatal if Swallowed. Do not drink antifreeze or solution. Avoid eye and prolonged or repeated skin contact. Avoid breathing vapors or mists. Wash exposed skin thoroughly with soap and water after use. Do not store in opened or unlabeled containers. Keep container away from open flames and excessive heat. Do not reuse empty containers unless properly cleaned. Empty containers retain product residue and may be dangerous. Do not cut, weld, drill, etc. containers, even empty.

Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without any obvious ignition sources. Published "autoignition" or "ignition" temperatures cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Use of this product in elevated temperature applications should be thoroughly evaluated to assure safe operating conditions.

**CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:** Store away from excessive heat and oxidizers.

**NFPA CLASSIFICATION:** III B

**8. Exposure Controls / Personal Protection**

**EXPOSURE GUIDELINES**

CHEMICAL	EXPOSURE LIMIT
Ethylene Glycol	25 ppm TWA, 50 ppm STEL ACGIH TLV (as vapor) 10 mg/m <sup>3</sup> TWA ACGIH TLV (as inhalable fraction of the aerosol)
Diethylene Glycol	10 mg/m <sup>3</sup> TWA AIHA WEEL

**APPROPRIATE ENGINEERING CONTROLS:** Use general ventilation or local exhaust as required to maintain exposures below the occupational exposure limits.

**PERSONAL PROTECTIVE EQUIPMENT**

**RESPIRATORY PROTECTION:** For operations where the occupational exposure limit is exceeded a NIOSH approved respirator with organic vapor cartridges and dust/mist prefilters or supplied air respirator is recommended. Equipment selection depends on contaminant type and concentration. Select and use in accordance with 29 CFR 1910.134 and good industrial



hygiene practice. For firefighting, use self-contained breathing apparatus.

GLOVES: Chemical resistant gloves such as neoprene or PVC where contact is possible.

EYE PROTECTION: Splash-proof goggles.

OTHER PROTECTIVE EQUIPMENT/CLOTHING: Appropriate protective clothing as needed to minimize skin contact.

### 9. Physical and Chemical Properties

APPEARANCE:	Clear, red liquid	ODOR:	Characteristic odor
ODOR THRESHOLD:	Not determined	pH:	8.1-8.7
MELTING/FREEZING POINT:	-34°F (-36.7°C)	BOILING POINT/RANGE:	Not determined
FLASH POINT:	>215°F (>101.7°C) TCC	EVAPORATION RATE:	Not determined
FLAMMABILITY (SOLID, GAS)	Not Applicable	FLAMMABILITY LIMITS:	LEL: 3.2% (ethylene glycol) UEL: 15.3% (ethylene glycol)
VAPOR PRESSURE:	< 0.1 mmHg @ 20°C	VAPOR DENSITY:	2.1
RELATIVE DENSITY:	1.07-1.08	SOLUBILITIES	Water: 100 %
PARTITION COEFFICIENT (n-octanol/water)	Not determined	AUTOIGNITION TEMPERATURE:	Not determined
DECOMPOSITION TEMPERATURE:	Not determined	VISCOSITY:	Not determined

### 10. Stability and Reactivity

REACTIVITY: Normally unreactive

CHEMICAL STABILITY: Stable

POSSIBILITY OF HAZARDOUS REACTIONS: Reaction with strong oxidizers will generate heat.

CONDITIONS TO AVOID: None known

INCOMPATIBLE MATERIALS: Avoid strong bases at high temperatures, strong acids, strong oxidizing agents, and materials reactive with hydroxyl compounds.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide.

### 11. Toxicological Information

#### POTENTIAL HEALTH EFFECTS:

##### ACUTE HAZARDS:

INHALATION: May cause irritation of the nose and throat with headache, particularly from mists. High vapor concentrations caused, for example, by heating the material in an enclosed and poorly ventilated workplace, may produce nausea, vomiting, headache, dizziness and irregular eye movements.

SKIN CONTACT: No evidence of adverse effects from available information.

EYE CONTACT: Liquid, vapors or mist may cause discomfort in the eye with persistent conjunctivitis, seen as slight excess redness or conjunctiva. Serious corneal injury is not anticipated.



**INGESTION:** May cause abdominal discomfort or pain, nausea, vomiting, dizziness, drowsiness, malaise, blurring of vision, irritability, back pain, decrease in urine output, kidney failure, and central nervous system effects, including irregular eye movements, convulsions and coma. Cardiac failure and pulmonary edema may develop. Severe kidney damage which may be fatal may follow the swallowing of ethylene glycol. A few reports have been published describing the development of weakness of the facial muscles, diminishing hearing, and difficulty with swallowing, during the late stages of severe poisoning.

**CHRONIC EFFECTS:** Prolonged or repeated inhalation exposure may produce signs of central nervous system involvement, particularly dizziness and jerking eye movements. Prolonged or repeated skin contact may cause skin sensitization and an associated dermatitis in some individuals. Ethylene glycol has been found to cause birth defects in laboratory animals. The significance of this finding to humans has not been determined.

**CARCINOGENICITY LISTING:** None of the components of these products is listed as a carcinogen or suspected carcinogen by IARC, NTP, ACGIH or OSHA.

**ACUTE TOXICITY VALUES:**

- Ethylene Glycol:           LD50 Oral Rat: 4700 mg/kg;  
                                  LD50 Skin Rabbit: 9530 mg/kg
  
- Diethylene Glycol:       LD50 Oral Rat: 12,565 mg/kg;  
                                  LD50 Skin Rabbit: 11,890 mg/kg

**SIGNIFICANT LABORATORY DATA WITH POSSIBLE RELEVANCE TO HUMAN HEALTH:** Ethylene glycol has been shown to produce dose-related teratogenic effects in rats and mice when given by gavage or in drinking water at high concentrations or doses. Also, in a preliminary study to assess the effects of exposure of pregnant rats and mice to aerosols at concentrations 150, 1,000 and 2,500 mg/m<sup>3</sup> for 6 hours a day throughout the period of organogenesis, teratogenic effects were produced at the highest concentrations, but only in mice. The conditions of these latter experiments did not allow a conclusion as to whether the developmental toxicity was mediated by inhalation of aerosol, percutaneous absorption of ethylene glycol from contaminated skin, or swallowing of ethylene glycol as a result of grooming the wetted coat. In a further study, comparing effects from high aerosol concentration by whole-body or nose-only exposure, it was shown that nose-only exposure resulted in maternal toxicity (1,000 and 2,500 mg/m<sup>3</sup>) and developmental toxicity in with minimal evidence of teratogenicity (2,500 mg/m<sup>3</sup>). The no-effects concentration (based on maternal toxicity) was 500 mg/m<sup>3</sup>. In a further study in mice, no teratogenic effects could be produced when ethylene glycol was applied to the skin of pregnant mice over the period of organogenesis. The above observations suggest that ethylene glycol is to be regarded as an animal teratogen; there is currently no available information to suggest that ethylene glycol caused birth defects in humans. Cutaneous application of ethylene glycol is ineffective in producing developmental toxicity; exposure to high aerosol concentration is only minimally effective in producing developmental toxicity; the major route for producing developmental toxicity is perorally.

Two chronic feeding studies, using rats and mice, have not produced any evidence that ethylene glycol causes dose-related increases in tumor incidence or a different pattern of tumors compared with untreated controls. The absence of carcinogenic potential for ethylene glycol has been supported by numerous invitro genotoxicity studies showing that it does not produce mutagenic or clastogenic effects.

**12. Ecological Information**

**ECOTOXICITY:**

- Ethylene Glycol: LC50 Fathead Minnow <10,000 mg/L/96 hr
- EC50 Daphnia Magna 100,000 mg/L/48 hr
- Bacterial (*Pseudomonas putida*): 10,000 mg/l
- Protozoa (*Entosiphon sulcatum* and *Uronema parduczi*; Chatton-Lwoff): >10,000 mg/l
- Algae (*Microcystis aeruginosa*): 2,000 mg/l
- Green algae (*Scenedesmus quadricauda*): >10,000 mg/l
- Diethylene Glycol: LC50 western mosquitofish >32,000 mg/L/96 hr





**PERSISTENCE AND DEGRADABILITY:**

Ethylene Glycol is readily biodegradable (97-100% in 2-12 days). Diethylene glycol is readily biodegradable (>70% in 19 days).

**BIOACCUMULATIVE POTENTIAL:**

Ethylene glycol: A BCF of 10, reported for ethylene glycol in fish, Golden ide (*Leuciscus idus melanotus*), after 3 days of exposure suggests the potential for bioconcentration in aquatic organisms is low.  
 Diethylene glycol: An estimated BCF of 3 suggests the potential for bioconcentration in aquatic organisms is low.

**MOBILITY IN SOIL:** Ethylene glycol and diethylene glycol are highly mobile in soil.

**OTHER ADVERSE EFFECTS:** None known

**13. Disposal Considerations**

Dispose of product in accordance with all local, state/provincial and federal regulations.

**14. Transport Information**

**U.S. DOT HAZARD CLASSIFICATION:** Not Regulated (unless package contains a reportable quantity)

**Note: IF A SHIPMENT OF A REPORTABLE QUANTITY (8333 LBS/998 GAL) IN A SINGLE PACKAGE IS INVOLVED, THE FOLLOWING INFORMATION APPLIES:**

**PROPER SHIPPING NAME:** RQ, Environmentally hazardous substance, liquid, n.o.s. (Ethylene glycol)  
**UN NUMBER:** UN3082  
**PACKING GROUP:** III  
**LABELS REQUIRED:** Class 9

**DOT MARINE POLLUTANTS:** This product does not contain Marine Pollutants as defined in 49 CFR 171.8.

**IMDG CODE SHIPPING CLASSIFICATION:** Not Regulated

**CANADIAN TDG CLASSIFICATION:** Not Regulated

**15. Regulatory Information**

**EPA SARA 311/312 HAZARD CLASSIFICATION:** Refer to Section 2 for OSHA Hazard Classification.

**EPA SARA 313:** This Product Contains the Following Chemicals Subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372):

Ethylene Glycol	107-21-1	40-60%
-----------------	----------	--------

**PROTECTION OF STRATOSPHERIC OZONE:** This product is not known to contain or to have been manufactured with ozone depleting substances as defined in 40 CFR Part 82, Appendix A to Subpart A.

**CERCLA SECTION 103:** Spills of this product over the RQ (reportable quantity) must be reported to the National Response Center. The RQ for this product, based on the RQ for Ethylene Glycol (100% maximum) of 5,000 lbs., is 5,000 lbs. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

**CALIFORNIA PROPOSITION 65:** This product contains the following chemicals regulated under California Proposition 65:

Ethylene Glycol	107-21-1	40-60%	developmental
-----------------	----------	--------	---------------



EPA TSCA INVENTORY: All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

CANADIAN ENVIRONMENTAL PROTECTION ACT: All of the ingredients are listed on the Canadian Domestic Substances List.

KOREA: All of the ingredients of this product are listed on the Korean Existing Chemical List (KECL).

CHINA: All of the ingredients of this product are listed on the Inventory of Existing Chemical Substances in China (IECSC).

PHILIPPINES: All of the ingredients of this product are listed on the Philippine Inventory of Chemical and Chemical Substance (PICCS)

<b>16. Other Information</b>
------------------------------

NFPA RATING (NFPA 704) - FIRE: 1      HEALTH: 2      REACTIVITY: 0

REVISION SUMMARY: Section 1 Added Product Numbers

SDS Date of Preparation/Revision: June 16, 2019

This SDS is directed to professional users and bulk handlers of the product. Consumer products are labeled in accordance with Federal Hazardous Substances Act regulations.

While Prestone Products Corporation believes that the data contained herein are factual and the opinions expressed are those of qualified experts regarding the results of the tests conducted, the data are not to be taken as a warranty or representation for which Prestone Products Corporation assumes legal responsibility. They are offered solely for your consideration, investigation and verification. Any use of these data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.